

# PRODUCT FAMILY DATASHEET

## LED SUPERSTAR GIMBLE DOWNLIGHT

LED DOWNLIGHT LUMINAIRES



### Overview

COB recessed downlight series designed with high ingress protection reaches to IP44, make it a good choice to use in all applications. LED light source with a wide range of lighting solutions and optics for all your lighting needs. Die-cast aluminum fitting with good thermal management that guarantees long life span. Suitable for Artwork, Galleries, Fashion stores, Shopping malls Museums and other commercial applications.

### Areas Of Application

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Foyers
- Shops

## TECHNICAL DATA

Product description	Electrical data			Photometrical data		Dimensions & weight			Colors & materials		Temperatures & operating conditions
	wattage.	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Width	Height	Product weight	Body material	Product color	Ambient temperature range
GIMBLE DOWNLIGHT LED 10 W 3000 K KIT	10.00 W	220...240 V	50 Hz	3000 K	920 lm	105.0 mm	71.5 mm	280.00 g	Polycarbonate (PC)	White	-20...45 °C
GIMBLE DOWNLIGHT LED 10 W 3000 K KIT	10.00 W	220...240 V	50 Hz	3000 K	920 lm	105.0 mm	71.5 mm	280.00 g	Polycarbonate (PC)	White	-20...45 °C
GIMBLE DOWNLIGHT LED 10 W 3000 K KIT	10.00 W	220...240 V	50 Hz	3000 K	920 lm	105.0 mm	71.5 mm	280.00 g	Polycarbonate (PC)	White	-20...45 °C
GIMBLE DOWNLIGHT LED 10 W 3000 K KIT	10.00 W	220...240 V	50 Hz	3000 K	920 lm	105.0 mm	71.5 mm	280.00 g	Polycarbonate (PC)	White	-20...45 °C

Product description	Lifespan	Capabilities	Certificates & standards	
	Lifespan	Dimmable	Protection class	Type of protection
GIMBLE DOWNLIGHT LED 10 W 3000 K KIT	30000 h	Yes	II	IP40
GIMBLE DOWNLIGHT LED 10 W 3000 K KIT	30000 h	Yes	II	IP40
GIMBLE DOWNLIGHT LED 10 W 3000 K KIT	30000 h	Yes	II	IP40
GIMBLE DOWNLIGHT LED 10 W 3000 K KIT	30000 h	Yes	II	IP40

## APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075132375	GIMBLE DOWNLIGHT LED 10 W 3000 K KIT	Shipping carton box 24	383 mm x 303 mm x 311 mm	36.09 dm <sup>3</sup>	9379.00 g
4058075132375	GIMBLE DOWNLIGHT LED 10 W 3000 K KIT	Shipping carton box 24	383 mm x 303 mm x 311 mm	36.09 dm <sup>3</sup>	9379.00 g
4058075132375	GIMBLE DOWNLIGHT LED 10 W 3000 K KIT	Shipping carton box 24	383 mm x 303 mm x 311 mm	36.09 dm <sup>3</sup>	9379.00 g
4058075132375	GIMBLE DOWNLIGHT LED 10 W 3000 K KIT	Shipping carton box 24	383 mm x 303 mm x 311 mm	36.09 dm <sup>3</sup>	9379.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.