

Packing List

Consignee: AHMED ABID AL-SHEIKH Trading CO.

Attention: Turkey Ahmed Abed Al-Sheikh

Tel: +966 12 620 5171

Address: KILO-08, Jeddah, Jeddah, Saudi Arabia

From: ATC MIDDLE EAST FZCO

Attention: Echo Chan

Tel: 008615018796671

Address: JAFZA One, 11th Floor, Jebel Ali Free Zone , Dubai, UAE

Shipment Number: 010401250209

Order Number:

0135,0172,0184,0199,0202,0203,0226

Date: 22/01/2025

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
1	TRHU5042712 40HQ	PR-DL-LOR36-02-043660	Premium - Lor - Down Light Recessed 36watt 4000K - CRI 80 3240Lumen - IP 20 - OSRAM LED Round D225 x H65mm White / Die-cast aluminum (Housing) - 5 Year Warranty	2,000	20	100	1776	2119	0.1036	10.3574 m ³
2		PR-EXL-FLA240-02-042822	Premium - Flare - Explosion Light Surface, Suspended, Mounted with bracket 240watt 5500K - CRI 70 28800Lumen - IP 66 - CREE LED Round D400 x H175mm Grey / Die-cast aluminum (Housing) - 5 Year Warranty	12	1	12	132	144	0.0407	0.4879 m ³
3		AS30149-A (RFE-0269A)	E-Series - Anis - Floodlight Mounted with bracket 150watt 3000K - CRI 80 12249Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W338 x L232 x H38mm Transparent / Glass (Front Cover) - White / Aluminum (Housing) - 3 Year Warranty Certified CB	6	6	1	14.6	16.4	0.0309	0.0309 m ³
4		AS60150-A (RFE-0268A)	E-Series - Anis - Floodlight Mounted with bracket 150watt 6500K - CRI 80 12997Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W338 x L232 x H38mm Transparent / Glass (Front Cover) - White / Aluminum (Housing) - 3 Year Warranty Certified CB	6	6	1	14.6	16.4	0.0309	0.0309 m ³
5		AS30151-C	E-Series - Anis - Floodlight Mounted with bracket with lens 200watt 3000K - CRI 80 15778Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W408 x L280 x H40mm Transparent / PC (Lens) - White / Aluminum (Housing) - 3 Year Warranty Certified CB	288	4	72	1015.2	1130.4	0.0257	1.8523 m ³
6		AS30151-A (RFE-0271A)	E-Series - Anis - Floodlight Mounted with bracket 200watt 3000K - CRI 80 15778Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W408 x H40mm Transparent / Glass (Front Cover) - White / Aluminum (Housing) - 3 Year Warranty Certified CB	4	4	1	14.1	15.7	0.0257	0.0257 m ³
7		AS60152-C	E-Series - Anis - Floodlight Mounted with bracket with lens 200watt 6500K - CRI 80 17077Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W408 x L280 x H40mm Transparent / PC (Lens) - White / Aluminum (Housing) - 3 Year Warranty Certified CB	1,472	4	368	5188.8	5777.6	0.0257	9.4675 m ³
8		AS60152-A (RFE-0270A)	E-Series - Anis - Floodlight Mounted with bracket 200watt 6500K - CRI 80 17077Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W408 x L280 x H40mm Transparent / Glass (Front Cover) - White / Aluminum (Housing) - 3 Year Warranty Certified CB	4	4	1	14.1	15.7	0.0257	0.0257 m ³
9		AS30153-C	E-Series - Anis - Floodlight Mounted with bracket with lens 300watt 3000K - CRI 80 23636Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W473 x L335 x H45mm Transparent / PC (Lens) - White / Aluminum (Housing) - 3 Year Warranty Certified CB	474	3	158	2385.8	2638.6	0.03	4.735 m ³
10		AS60154-C	E-Series - Anis - Floodlight Mounted with bracket with lens 300watt 6500K - CRI 80 25279Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W473 x L335 x H45mm Transparent / PC (Lens) - White / Aluminum (Housing) - 3 Year Warranty Certified CB	996	3	332	5013.2	5544.4	0.03	9.9495 m ³
11		SF30001-A	Comfortlife - Safari - Floodlight Surface 5watt 3000K - CRI 80 500Lumen - Battery Voltage 3.7- Battery Capacity 3000- Battery Type Li-ion- Panel Output Voltage 5- Solar Panel Type mono-crystalline - Solar Panel Power 2.3- IP 65 - Rectangular W149.62 x L231.9 x H33.68mm Black / ABS (Housing) - Transparent / plastic (Housing) - 2 Year Warranty Certified CB	990	18	55	633.6	759	0.0343	1.8871 m ³
12		SF30001-B	Comfortlife - Safari - Floodlight Surface 5watt 6000K - CRI 80 550Lumen - Battery Voltage 3.7- Battery Capacity 3000- Battery Type Li-ion- Panel Output Voltage 5- Solar Panel Type mono-crystalline - Solar Panel Power 2.3- IP 65 - Rectangular W149.62 x L231.9 x H33.68mm Black / ABS (Housing) - Transparent / plastic (Housing) - 2 Year Warranty Certified CB	990	18	55	633.6	759	0.0343	1.8871 m ³
13		LM30450-C	E-Series - Lamsa - Table Lamp Free standing Dimmable Built-in touch dimmer 3watt 3000K - CRI 80 240Lumen - IP 52 - OSRAM LED T Shape D112 x H370mm White / Iron (Base) - White / Iron (Pole) - White / Iron (Lampshade) - 2 Year Warranty	480	20	24	393.6	436.8	0.1879	4.5101 m ³
14		LM30445-C	E-Series - Lamsa - Table Lamp Free standing Dimmable Built-in touch dimmer 3watt 3000K - CRI 80 240Lumen - IP 52 - OSRAM LED T Shape D112 x H370mm Black / Iron (Base) - Black / Iron (Pole) - Black / Iron (Lampshade) - 2 Year Warranty	480	20	24	393.6	436.8	0.1879	4.5101 m ³

Stamp



62305417

Signature

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
15	TRHU5042712 40HQ	LMR0443-C	E-Series - Lamsa - Table Lamp Free standing Dimmable Built-in touch dimmer 3watt RGBW - 240Lumen - -IP 52 - T Shape D112 x H370mm White / Iron (Base) - White / Iron (Pole) - White / Iron (Lampshade) - 2 Year Warranty	480	20	24	393.6	436.8	0.1879	4.5101 m ³
16		LMR0449-C	E-Series - Lamsa - Table Lamp Free standing Dimmable Built-in touch dimmer 3watt RGBW - 240Lumen - -IP 52 - T Shape D112 x H370mm Black / Iron (Base) - Black / Iron (Pole) - Black / Iron (Lampshade) - 2 Year Warranty	480	20	24	393.6	436.8	0.1879	4.5101 m ³
17		ES-0526A (RFE-0134A)	Plug For Strips 220V 50m 2835 12mm, Connected to electric plug type C. Non CB	1,200	200	6	42	48	0.042	0.252 m ³
18		AS121-11A	Electric - Asala - Blank Plate - - White / PC (Base), White / PC (Frame) - W146 x L86	400	100	4	52	62	0.0333	0.1333 m ³
19		AS121-22A	Electric - Asala - Blank Plate - - Black / PC (Base), Black / PC (Frame) - W146 x L86	400	100	4	52	62	0.0333	0.1333 m ³
20		EQ0754	18650 Rechargeable battery, lithium-ion, Type-C charging 5VDC/700mA, with charging cable, 3.7V, 2000mAh, 7400mWh, charging time 3-3.5h, long life ≥ 1000 cycles, max discharge current 5A, 1 year warranty, Operating temperature -20° / +60° C, Weight 40g, D18xH65mm.	90	90	1	5.6	6.8	0.0293	0.0293 m ³
21		EQ0702	Collapsed mosquito trap, Built-in 2000mAh li battery UV wave length: 0.06W 360-400nm, 0.1W 2835 390-400nm, Grid voltage ≥ 2000V Size: 290*200*80mm Material: ABS+PC Working time after full charge : about 12 hours Flying insects killer with two ways to use ,can be used without opening as a normal mosquito killer put on any surface ,table ,desk or on the floor ,or the handle can be opened and the trap can be used as a swatter (club shaped) ,this device comes with USB charging cable to charge the built in Li-ion battery can last for about 12 hours after a full charge, full charging may take from 4-5 hours , with an indicator that goes red while charging and green when is fully charged	495	5	99	900.9	990	0.0661	6.5459 m ³
22		EQ0756	9V Rechargeable battery, lithium-ion, Type-C charging 5VDC/500mA, with charging cable, 9V, 400mAh, 3700mWh, charging time 2-2.5h, long life ≥ 1000 cycles, max discharge current 150mA, 1 year warranty, Operating temperature -20° / +60° C, Weight 24g, 48.1*26*16.8mm	360	90	4	17.2	22	0.0293	0.1172 m ³
23		EQ0751	AAA Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/250mA, with 2in1 cable, 1.5V, 580mAh, 880mWh, charging time 1-2h, long life ≥ 1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature -20° / +60° C, Weight 8.5g, D10xH44mm.	800	160	5	30	36	0.0293	0.1465 m ³
24		EQ0819	Metal Display Stand, 0.7mm Iron Size:W250xBase Depth250xH500mm with 4pcs of 200mm length pegboard hooks Printing Part: Material: 5mm thickness PVC	40	1	40	80	100	0.014	0.561 m ³
25		EQ0747	AA Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 1700mAh, 2600mWh, charging time 1-2h, long life ≥ 1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60° C, Weight 18g, D14xH50mm.	1,320	120	11	99	112.2	0.0293	0.3222 m ³
26		EQ0748	AAA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/120mA, with 4in1 cable, 1.5V, 440mAh, 660mWh, charging time 1-2h, long life ≥ 1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature -20° / +60° C, Weight 8g, D10xH44mm.	160	160	1	8.3	9.5	0.0293	0.0293 m ³
27		EQ0743	AA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/500mA, with 4in1 cable, 1.5V, 1460mAh, 2220mWh, charging time 1-2h, long life ≥ 1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60° C, Weight 16g, D14xH50mm.	240	120	2	21.4	23.8	0.0293	0.0586 m ³
28		EQ0749	AAA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/250mA, with 4in1 cable, 1.5V, 580mAh, 880mWh, charging time 1-2h, long life ≥ 1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature -20° / +60° C, Weight 8.5g, D10xH44mm.	1,280	160	8	74.4	84	0.0293	0.2344 m ³
29		EQ0744	AA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/500mA, with 4in1 cable, 1.5V, 1700mAh, 2600mWh, charging time 1-2h, long life ≥ 1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60° C, Weight 18g, D14xH50mm.	1,320	120	11	176	189.2	0.0293	0.3222 m ³
30		EQ0752	D type Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 4900mAh, 7400mWh, charging time~ 5h, long life ≥ 1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60° C, Weight 80.5g, D32xH61mm.	100	50	2	18	20.4	0.0293	0.0586 m ³
31		EQ0753	C type Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 4900mAh, 7400mWh, charging time~ 5h, long life ≥ 1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60° C, Weight 55.5g, D25.2xH50.5mm.	60	60	1	7.8	9	0.0293	0.0293 m ³

Stamp



62305417

2 of 7

Powered By LUMYTIC

Signature

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
---	------------------	-------------	------	----------	---------	-----	----------	----------	-------------	--------------

Stamp



Signature

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
32	TRHU5042712 40HQ	EQ0818	Metal Display Stand, 0.7mm Iron Size:W500xBase Depth450xH1500mm with 28pcs of 200mm length pegboard hooks Printing Part: Material: 5mm thickness PVC Cable Part: 300mm x 170mm	25	1	25	300	321.25	0.0509	1.2719 m ³

Stamp



Signature

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
33		SF30001-A	Comfortlife – Safari – Floodlight Surface 5watt 3000K – CRI 80 500Lumen – Battery Voltage 3.7– Battery Capacity 3000– Battery Type Li-ion– Panel Output Voltage 5– Solar Panel Type mono-crystalline – Solar Panel Power 2.3 – –IP 65 – Rectangular W149.62 x L231.9 x H33.68mm Black / ABS (Housing) – Transparent / plastic (Housing) – 2 Year Warranty Certified CB	16						
34		EQ0702	Collapsed mosquito trap, Built-in 2000mAh li battery UV wave length: 0.06W 360–400nm, 0.1W 2835 390–400nm, Grid voltage ≥ 2000V Size: 290*200*80mm Material: ABS+PC Working time after full charge : about 12 hours Flying insects killer with two ways to use ,can be used without opening as a normal mosquito killer put on any surface ,table ,desk or on the floor ,or the handle can be opened and the trap can be used as a swatter (club shaped) ,this device comes with USB charging cable to charge the built in Li-ion battery can last for about 12 hours after a full charge, full charging may take from 4–5 hours , with an indicator that goes red while charging and green when is fully charged	3						
35		EQ0750	AAA Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/120mA, with 2in1 cable, 1.5V, 440mAh, 660mWh, charging time 1–2h, long life ≥ 1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature –20° / +60° C, Weight 8g, D10xH44mm.	153						
36		EQ0756	9V Rechargeable battery, lithium-ion, Type-C charging 5VDC/500mA, with charging cable, 9V, 400mAh, 3700mWh, charging time 2–2.5h, long life ≥ 1000 cycles, max discharge current 150mA, 1 year warranty, Operating temperature –20° / +60° C, Weight 24g, 48.1*26*16.8mm	83	–	1	11.52	13.8	–	0.0343 m ³
37		EQ0751	AAA Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/250mA, with 2in1 cable, 1.5V, 580mAh, 880mWh, charging time 1–2h, long life ≥ 1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature –20° / +60° C, Weight 8.5g, D10xH44mm.	153						
38		EQ0755	16340 Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/320mA, with 2in1 cable, 3.7V, 700mAh, 2500mWh, charging time 2–2.5h, long life ≥ 1000 cycles, max discharge current 3A, 1 year warranty, Operating temperature –20° / +60° C, Weight 19g, D16xH35mm.	93						
39		EQ0749	AAA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/250mA, with 4in1 cable, 1.5V, 580mAh, 880mWh, charging time 1–2h, long life ≥ 1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature –20° / +60° C, Weight 8.5g, D10xH44mm.	153						
40		EQ0752	D type Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 4900mAh, 7400mWh, charging time~ 5h, long life ≥ 1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature –20° / +60° C, Weight 80.5g, D32xH61mm.	43						
41		EQ0753	C type Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 4900mAh, 7400mWh, charging time~ 5h, long life ≥ 1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature –20° / +60° C, Weight 55.5g, D25.2xH50.5mm.	53						
42		SF30001-B	Comfortlife – Safari – Floodlight Surface 5watt 6000K – CRI 80 550Lumen – Battery Voltage 3.7– Battery Capacity 3000– Battery Type Li-ion– Panel Output Voltage 5– Solar Panel Type mono-crystalline – Solar Panel Power 2.3 – –IP 65 – Rectangular W149.62 x L231.9 x H33.68mm Black / ABS (Housing) – Transparent / plastic (Housing) – 2 Year Warranty Certified CB	16	–	1	11.52	13.8	–	0.0343 m ³
43		SA40298-A	E-Series – Sari – High Bay Suspendant 150watt 4000K – CRI 70 12750Lumen – 0.9PF 175 To 265V IP 65 – LUMILEDS LED Round D310 x H88mm Black / Aluminum (Housing) – 2100g – 2 Year Warranty Certified CB	2						
44		AS121-11A	Electric – Asala – Blank Plate – – White / PC (Base), White / PC (Frame) – W146 x L86	95	–	1	14	15.28	–	0.0418 m ³
45		AS121-22A	Electric – Asala – Blank Plate – – Black / PC (Base), Black / PC (Frame) – W146 x L86	95	–	1	14	15.28	–	0.0418 m ³
46		LM30445-C	E-Series – Lamsa – Table Lamp Free standing Dimmable Built-in touch dimmer 3watt 3000K – CRI 80 240Lumen – –IP 52 – OSRAM LED T Shape D112 x H370mm Black / Iron (Base) – Black / Iron (Pole) – Black / Iron (Lampshade) – 2 Year Warranty	18	–	1	13.6	18.5	–	0.1796 m ³
47		LM30450-C	E-Series – Lamsa – Table Lamp Free standing Dimmable Built-in touch dimmer 3watt 3000K – CRI 80 240Lumen – –IP 52 – OSRAM LED T Shape D112 x H370mm White / Iron (Base) – White / Iron (Pole) – White / Iron (Lampshade) – 2 Year Warranty	18	–	1	13.6	15.8	–	0.1796 m ³
48		LMR0443-C	E-Series – Lamsa – Table Lamp Free standing Dimmable Built-in touch dimmer 3watt RGBW – 240Lumen – –IP 52 – T Shape D112 x H370mm White / Iron (Base) – White / Iron (Pole) – White / Iron (Lampshade) – 2 Year Warranty	18	–	1	13.6	18.5	–	0.1796 m ³

Stamp



62305417

5 of 7

Powered By LUMYTIC

Signature

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
49	TRHU5042712 40HQ	LMR0449-C	E-Series – Lamsa – Table Lamp Free standing Dimmable Built-in touch dimmer 3watt RGBW – 240Lumen – –IP 52 – T Shape D112 x H370mm Black / Iron (Base) – Black / Iron (Pole) – Black / Iron (Lampshade) – 2 Year Warranty	18	–	1	13.6	18.5	–	0.1796 m ³
50		AS30149-A (RFE-0269A)	E-Series – Anis – Floodlight Mounted with bracket 150watt 3000K – CRI 80 12249Lumen – 0.9PF 176 To 265V IP 65 – Rectangular W338 x L232 x H38mm Transparent / Glass (Front Cover) – White / Aluminum (Housing) – 3 Year Warranty Certified CB	5	–	1	14.6	16.4	–	0.0309 m ³
51		AS60150-A (RFE-0268A)	E-Series – Anis – Floodlight Mounted with bracket 150watt 6500K – CRI 80 12997Lumen – 0.9PF 176 To 265V IP 65 – Rectangular W338 x L232 x H38mm Transparent / Glass (Front Cover) – White / Aluminum (Housing) – 3 Year Warranty Certified CB	5	–	1	14.6	16.4	–	0.0309 m ³
52		AS30151-A (RFE-0271A)	E-Series – Anis – Floodlight Mounted with bracket 200watt 3000K – CRI 80 15778Lumen – 0.9PF 176 To 265V IP 65 – Rectangular W408 x L280 x H40mm Transparent / Glass (Front Cover) – White / Aluminum (Housing) – 3 Year Warranty Certified CB	3	–	1	14.1	15.7	–	0.0257 m ³
53		AS60152-A (RFE-0270A)	E-Series – Anis – Floodlight Mounted with bracket 200watt 6500K – CRI 80 17077Lumen – 0.9PF 176 To 265V IP 65 – Rectangular W408 x L280 x H40mm Transparent / Glass (Front Cover) – White / Aluminum (Housing) – 3 Year Warranty Certified CB	3	–	1	14.1	15.7	–	0.0257 m ³
54		AS60152-C	E-Series – Anis – Floodlight Mounted with bracket with lens 200watt 6500K – CRI 80 17077Lumen – 0.9PF 176 To 265V IP 65 – Rectangular W408 x L280 x H40mm Transparent / PC (Lens) – White / Aluminum (Housing) – 3 Year Warranty Certified CB	6	–	1	11.2	12.6	–	0.0257 m ³
55		AS60154-C	E-Series – Anis – Floodlight Mounted with bracket with lens 300watt 6500K – CRI 80 25279Lumen – 0.9PF 176 To 265V IP 65 – Rectangular W473 x L335 x H45mm Transparent / PC (Lens) – White / Aluminum (Housing) – 3 Year Warranty Certified CB	4	–	1	11.9	13.4	–	0.03 m ³
56		AS30151-C	E-Series – Anis – Floodlight Mounted with bracket with lens 200watt 3000K – CRI 80 15778Lumen – 0.9PF 176 To 265V IP 65 – Rectangular W408 x L280 x H40mm Transparent / PC (Lens) – White / Aluminum (Housing) – 3 Year Warranty Certified CB	3	–	1	11.2	12.6	–	0.0257 m ³
57		AS30153-C	E-Series – Anis – Floodlight Mounted with bracket with lens 300watt 3000K – CRI 80 23636Lumen – 0.9PF 176 To 265V IP 65 – Rectangular W473 x L335 x H45mm Transparent / PC (Lens) – White / Aluminum (Housing) – 3 Year Warranty Certified CB	2	–	1	11.9	13.4	–	0.03 m ³
58		EQ0743	AA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/500mA, with 4in1 cable, 1.5V, 1460mAh, 2220mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60° C, Weight 16g, D14xH50mm.	113	–	1	9.9	11.3	–	0.0293 m ³
59		EQ0744	AA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/500mA, with 4in1 cable, 1.5V, 1700mAh, 2600mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60° C, Weight 18g, D14xH50mm.	113	–	1	9.7	11.1	–	0.0356 m ³
60		EQ0746	AA Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 1460mAh, 2220mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60° C, Weight 16g, D14xH50mm.	113	–	1	5.8	7.3	–	0.0293 m ³
61		EQ0747	AA Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 1700mAh, 2600mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60° C, Weight 18g, D14xH50mm.	113	–	1	5.7	7.2	–	0.0293 m ³
62		EQ0748	AAA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/120mA, with 4in1 cable, 1.5V, 440mAh, 660mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature -20° / +60° C, Weight 8g, D10xH44mm.	153	–	1	7.9	9.3	–	0.0293 m ³
63		EQ0754	18650 Rechargeable battery, lithium-ion, Type-C charging 5VDC/700mA, with charging cable, 3.7V, 2000mAh, 7400mWh, charging time 3-3.5h, long life ≥1000 cycles, max discharge current 5A, 1 year warranty, Operating temperature -20° / +60° C, Weight 40g, D18xH65mm.	83	–	1	5.1	6.5	–	0.0293 m ³
64		GF0897	LED Flood light	1	–	1	3	3.62	–	0.0181 m ³
65		GF0897	LED Flood light	1	–	1	5	5.12	–	0.02 m ³

Stamp



62305417

6 of 7

Powered By LUMYTIC

Signature

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
66	TRHU5042712 40HQ	GF0897	LED Flood light	1	–	1	4	5	–	0.0228 m ³
67		GF0897	LED Flood light	1	–	1	3	3.62	–	0.0189 m ³
68		GF0897	LED Flood light	1	–	1	6	7.02	–	0.0259 m ³
69		GF0897	LED Flood light	1	–	1	6	7.06	–	0.0282 m ³
70		GF0896	Outdoor light	1	–	1	1	1.04	–	0.0228 m ³
71		GF0895	Street light lamp	1	–	1	5	6.06	–	0.0305 m ³
72		GF0895	Street light lamp	1	–	1	6	6.24	–	0.0411 m ³
73		GF0893	Switch shell	10	–	1	5	5.62	–	0.0772 m ³
74		GF0894	Down light	6						
Total				19,226		1,508	20,592	23,128		70.6051 m³

Stamp



62305417

7 of 7

Powered By LUMYTIC

Signature