

## Packing List

**Consignee:** AHMED ABID AL-SHEIKH Trading CO.  
**Attention:** Turkey Ahmed Abed Al-Sheikh  
**Tel:** +966 12 620 5171  
**Address:** KILO-08, Jeddah, Jeddah, Saudi Arabia

**From:** ATC MIDDLE EAST FZCO  
**Attention:** Echo Chan  
**Tel:** 008615018796671  
**Address:** JAFZA One, 11th Floor, Jebel Ali Free  
Zone , Dubai, UAE

**Shipment Number:** 010411240209  
**Order Number:**  
0135,0172,0184,0199,0202,0203,0226  
**Date:** 20/11/2024

Stamp



84753916

Signature

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
1		043660	Premium - Lor Down Light - Led By OSRAM - 36W, 3240lum AC 220-240V, 4000K IP 20, CRI> 80, 90° - Round D225 x H65 - White / Die-cast aluminum (Housing) - 5 Year Warranty	2,000	20	100	1776	2119	0.1036	10.3574m³
2		AS30149-A (RFE-0269A)	E-Series - Anis - Floodlight Mounted with bracket <b>150watt 3000K</b> - CRI 80 12249Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W338 x L232 x H38mm</b> Transparent / Glass (Front Cover) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	6	6	1	14.6	16.4	0.0309	0.0309m³
3		AS60150-A (RFE-0268A)	E-Series - Anis - Floodlight Mounted with bracket <b>150watt 6500K</b> - CRI 80 12997Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W338 x L232 x H38mm</b> Transparent / Glass (Front Cover) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	6	6	1	14.6	16.4	0.0309	0.0309m³
4		AS30151-C	E-Series - Anis - Floodlight Mounted with bracket with lens <b>200watt 3000K</b> - CRI 80 15778Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W408 x L280 x H40mm</b> Transparent / PC (Lens) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	288	4	72	1015.2	1130.4	0.0257	1.8523m³
5		AS30151-A (RFE-0271A)	E-Series - Anis - Floodlight Mounted with bracket <b>200watt 3000K</b> - CRI 80 15778Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W408 x H40mm</b> Transparent / Glass (Front Cover) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	4	4	1	14.1	15.7	0.0257	0.0257m³
6		AS60152-C	E-Series - Anis - Floodlight Mounted with bracket with lens <b>200watt 6500K</b> - CRI 80 17077Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W408 x L280 x H40mm</b> Transparent / PC (Lens) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	1,472	4	368	5188.8	5777.6	0.0257	9.4675m³
7		AS60152-A (RFE-0270A)	E-Series - Anis - Floodlight Mounted with bracket <b>200watt 6500K</b> - CRI 80 17077Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W408 x H40mm</b> Transparent / Glass (Front Cover) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	4	4	1	14.1	15.7	0.0257	0.0257m³
8	020931 40HQ	AS30153-C	E-Series - Anis - Floodlight Mounted with bracket with lens <b>300watt 3000K</b> - CRI 80 23636Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W473 x L335 x H45mm</b> Transparent / PC (Lens) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	474	3	158	2385.8	2638.6	0.03	4.735m³
9		AS60154-C	E-Series - Anis - Floodlight Mounted with bracket with lens <b>300watt 6500K</b> - CRI 80 25279Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W473 x L335 x H45mm</b> Transparent / PC (Lens) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	996	3	332	5013.2	5544.4	0.03	9.9495m³
10		SF30001-A	Comfortlife - Safari - Floodlight Surface <b>5watt 3000K</b> - CRI 80 500Lumen - Battery Voltage 3.7- Battery Capacity 3000- Battery Type Li-ion- Panel Output Voltage 5- Solar Panel Type mono-crystalline - Solar Panel Power 2.3- -IP 65 - <b>Rectangular W149.62 x L231.9 x H33.68mm</b> Black / ABS (Housing) - Transparent / plastic (Housing) - <b>2 Year Warranty</b> Certified CB	990	18	55	633.6	759	0.0343	1.8871m³
11		SF30001-B	Comfortlife - Safari - Floodlight Surface <b>5watt 6000K</b> - CRI 80 550Lumen - Battery Voltage 3.7- Battery Capacity 3000- Battery Type Li-ion- Panel Output Voltage 5- Solar Panel Type mono-crystalline - Solar Panel Power 2.3- -IP 65 - <b>Rectangular W149.62 x L231.9 x H33.68mm</b> Black / ABS (Housing) - Transparent / plastic (Housing) - <b>2 Year Warranty</b> Certified CB	990	18	55	633.6	759	0.0343	1.8871m³
12		LM30445-C	E-Series - Lamsa - Table Lamp Free standing <b>Dimmable Built-in touch dimmer 3watt 3000K</b> - CRI 80 240Lumen - -IP 52 - <b>OSRAM LED T Shape D112 x H370mm</b> Black / Iron (Base) - Black / Iron (Pole) - Black / Iron (Lampshade) - <b>2 Year Warranty</b>	480	20	24	393.6	436.8	0.1879	4.5101m³
13		LM30450-C	E-Series - Lamsa - Table Lamp Free standing <b>Dimmable Built-in touch dimmer 3watt 3000K</b> - CRI 80 240Lumen - -IP 52 - <b>OSRAM LED T Shape D112 x H370mm</b> White / Iron (Base) - White / Iron (Pole) - White / Iron (Lampshade) - <b>2 Year Warranty</b>	480	20	24	393.6	436.8	0.1879	4.5101m³
14		LMR0443-C	E-Series - Lamsa - Table Lamp Free standing <b>Dimmable Built-in touch dimmer 3watt RGBW</b> - 240Lumen - -IP 52 - <b>T Shape D112 x H370mm</b> White / Iron (Base) - White / Iron (Pole) - White / Iron (Lampshade) - <b>2 Year Warranty</b>	480	20	24	393.6	436.8	0.1879	4.5101m³

Stamp



84753916

Signature

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
---	------------------	-------------	------	----------	---------	-----	----------	----------	-------------	--------------

**Stamp**



84753916

**Signature**

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
15		LMR0449-C	E-Series - Lamsa - Table Lamp Free standing <b>Dimmable Built-in touch dimmer 3watt RGBW</b> - 240Lumen - -IP 52 - <b>T Shape D112 x H370mm</b> Black / Iron (Base) - Black / Iron (Pole) - Black / Iron (Lampshade) - <b>2 Year Warranty</b>	480	20	24	393.6	436.8	0.1879	4.5101m <sup>3</sup>

020931  
40HQ

**Stamp**



84753916

**Signature**

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
16		ES-0526A (RFE-0134A)	Plug For Strips 220V 50m 2835 12mm, Connected to electric plug type C. Non CB	1,200	200	6	42	48	0.042	0.252m <sup>3</sup>
17		AS121-11A	Electric - Asala - Blank Plate - - White / PC (Base), White / PC (Frame) - W146 x L86	400	100	4	52	62	0.0333	0.1333m <sup>3</sup>
18		AS121-22A	Electric - Asala - Blank Plate - - Black / PC (Base), Black / PC (Frame) - W146 x L86	400	100	4	52	62	0.0333	0.1333m <sup>3</sup>
19		EQ0754	18650 Rechargeable battery, lithium-ion, Type-C charging 5VDC/700mA, with charging cable, 3.7V, 2000mAh, 7400mWh, charging time 3-3.5h, long life ≥1000 cycles, max discharge current 5A, 1 year warranty, Operating temperature -20° / +60°C, Weight 40g, D18xH65mm.	90	90	1	5.6	6.8	0.0293	0.0293m <sup>3</sup>
20		EQ0702	Collapsed mosquito trap, Built-in 2000mAh li battery UV wave length: 0.06W 360-400nm, 0.1W 2835 390-400nm, Grid voltage ≥2000V Size: 290*200*80mm Material: ABS+PC Working time after full charge : about 12 hours	495	5	99	900.9	990	0.0661	6.5459m <sup>3</sup>
21		EQ0756	9V Rechargeable battery, lithium-ion, Type-C charging 5VDC/500mA, with charging cable, 9V, 400mAh, 3700mWh, charging time 2-2.5h, long life ≥1000 cycles, max discharge current 150mA, 1 year warranty, Operating temperature -20° / +60°C, Weight 24g, 48.1*26*16.8mm	360	90	4	17.2	22	0.0293	0.1172m <sup>3</sup>
22		EQ0751	AAA Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/250mA, with 2in1 cable, 1.5V, 580mAh, 880mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature -20° / +60°C, Weight 8.5g, D10xH44mm.	800	160	5	30	36	0.0293	0.1465m <sup>3</sup>
23		EQ0819	Metal Display Stand, 0.7mm Iron Size:W250xBASE Depth250xH500mm with 4pcs of 200mm length pegboard hooks Printing Part: Material: 5mm thickness PVC Cable Part: 120mm x 80mm	40	1	40	80	100	0.014	0.561m <sup>3</sup>
24		EQ0747	AA Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 1700mAh, 2600mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60°C, Weight 18g, D14xH50mm.	1,320	120	11	99	112.2	0.0293	0.3222m <sup>3</sup>
25		EQ0748	AAA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/120mA, with 4in1 cable, 1.5V, 440mAh, 660mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature -20° / +60°C, Weight 8g, D10xH44mm.	160	160	1	8.3	9.5	0.0293	0.0293m <sup>3</sup>
26		EQ0743	AA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/500mA, with 4in1 cable, 1.5V, 1460mAh, 2220mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60°C, Weight 16g, D14xH50mm.	240	120	2	21.4	23.8	0.0293	0.0586m <sup>3</sup>
27		EQ0749	AAA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/250mA, with 4in1 cable, 1.5V, 580mAh, 880mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature -20° / +60°C, Weight 8.5g, D10xH44mm.	1,280	160	8	74.4	84	0.0293	0.2344m <sup>3</sup>
28		EQ0744	AA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/500mA, with 4in1 cable, 1.5V, 1700mAh, 2600mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60°C, Weight 18g, D14xH50mm.	1,320	120	11	176	189.2	0.0293	0.3222m <sup>3</sup>
29		EQ0752	D type Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 4900mAh, 7400mWh, charging time~ 5h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60°C, Weight 80.5g, D32xH61mm.	100	50	2	18	20.4	0.0293	0.0586m <sup>3</sup>
30		EQ0753	C type Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 4900mAh, 7400mWh, charging time~ 5h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60°C, Weight 55.5g, D25.2xH50.5mm.	60	60	1	7.8	9	0.0293	0.0293m <sup>3</sup>
31		EQ0818	Metal Display Stand, 0.7mm Iron Size:W500xBASE Depth450xH1500mm with 28pcs of 200mm length pegboard hooks Printing Part: Material: 5mm thickness PVC Cable Part: 300mm x 170mm	25	1	25	300	321.25	0.0509	1.2719m <sup>3</sup>

Stamp



84753916

Signature

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
32	020931 40HQ	SF30001-A	Comfortlife - Safari - Floodlight Surface <b>5watt 3000K</b> - CRI 80 500Lumen - Battery Voltage 3.7- Battery Capacity 3000- Battery Type Li-ion- Panel Output Voltage 5- Solar Panel Type mono-crystalline - Solar Panel Power 2.3- -IP 65 - <b>Rectangular W149.62 x L231.9 x H33.68mm</b> Black / ABS (Housing) - Transparent / plastic (Housing) - <b>2 Year Warranty</b> Certified CB	16	-	1	11.52	13.8	-	0.0343m <sup>3</sup>
33		SF30001-B	Comfortlife - Safari - Floodlight Surface <b>5watt 6000K</b> - CRI 80 550Lumen - Battery Voltage 3.7- Battery Capacity 3000- Battery Type Li-ion- Panel Output Voltage 5- Solar Panel Type mono-crystalline - Solar Panel Power 2.3- -IP 65 - <b>Rectangular W149.62 x L231.9 x H33.68mm</b> Black / ABS (Housing) - Transparent / plastic (Housing) - <b>2 Year Warranty</b> Certified CB	16	-	1	11.52	13.8	-	0.0343m <sup>3</sup>
34		AS121-11A	Electric - Asala - Blank Plate - - White / PC (Base), White / PC (Frame) - W146 x L86	95	-	1	14	15.28	-	0.0418m <sup>3</sup>
35		AS121-22A	Electric - Asala - Blank Plate - - Black / PC (Base), Black / PC (Frame) - W146 x L86	95	-	1	14	15.28	-	0.0418m <sup>3</sup>
36		LM30445-C	E-Series - Lamsa - Table Lamp Free standing <b>Dimmable Built-in touch dimmer 3watt 3000K</b> - CRI 80 240Lumen - -IP 52 - <b>OSRAM LED T Shape D112 x H370mm</b> Black / Iron (Base) - Black / Iron (Pole) - Black / Iron (Lampshade) - <b>2 Year Warranty</b>	18	-	1	13.6	18.5	-	0.1796m <sup>3</sup>
37		LM30450-C	E-Series - Lamsa - Table Lamp Free standing <b>Dimmable Built-in touch dimmer 3watt 3000K</b> - CRI 80 240Lumen - -IP 52 - <b>OSRAM LED T Shape D112 x H370mm</b> White / Iron (Base) - White / Iron (Pole) - White / Iron (Lampshade) - <b>2 Year Warranty</b>	18	-	1	13.6	15.8	-	0.1796m <sup>3</sup>
38		LMR0443-C	E-Series - Lamsa - Table Lamp Free standing <b>Dimmable Built-in touch dimmer 3watt RGBW</b> - 240Lumen - -IP 52 - <b>T Shape D112 x H370mm</b> White / Iron (Base) - White / Iron (Pole) - White / Iron (Lampshade) - <b>2 Year Warranty</b>	18	-	1	13.6	18.5	-	0.1796m <sup>3</sup>
39		LMR0449-C	E-Series - Lamsa - Table Lamp Free standing <b>Dimmable Built-in touch dimmer 3watt RGBW</b> - 240Lumen - -IP 52 - <b>T Shape D112 x H370mm</b> Black / Iron (Base) - Black / Iron (Pole) - Black / Iron (Lampshade) - <b>2 Year Warranty</b>	18	-	1	13.6	18.5	-	0.1796m <sup>3</sup>
40		AS30149-A (RFE-0269A)	E-Series - Anis - Floodlight Mounted with bracket <b>150watt 3000K</b> - CRI 80 12249Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W338 x L232 x H38mm</b> Transparent / Glass (Front Cover) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	5	-	1	14.6	16.4	-	0.0309m <sup>3</sup>
41		AS60150-A (RFE-0268A)	E-Series - Anis - Floodlight Mounted with bracket <b>150watt 6500K</b> - CRI 80 12997Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W338 x L232 x H38mm</b> Transparent / Glass (Front Cover) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	5	-	1	14.6	16.4	-	0.0309m <sup>3</sup>
42		AS30151-A (RFE-0271A)	E-Series - Anis - Floodlight Mounted with bracket <b>200watt 3000K</b> - CRI 80 15778Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W408 x L280 x H40mm</b> Transparent / Glass (Front Cover) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	3	-	1	14.1	15.7	-	0.0257m <sup>3</sup>
43		AS60152-A (RFE-0270A)	E-Series - Anis - Floodlight Mounted with bracket <b>200watt 6500K</b> - CRI 80 17077Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W408 x L280 x H40mm</b> Transparent / Glass (Front Cover) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	3	-	1	14.1	15.7	-	0.0257m <sup>3</sup>
44		AS60152-C	E-Series - Anis - Floodlight Mounted with bracket with lens <b>200watt 6500K</b> - CRI 80 17077Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W408 x L280 x H40mm</b> Transparent / PC (Lens) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	6	-	1	11.2	12.6	-	0.0257m <sup>3</sup>
45		AS60154-C	E-Series - Anis - Floodlight Mounted with bracket with lens <b>300watt 6500K</b> - CRI 80 25279Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W473 x L335 x H45mm</b> Transparent / PC (Lens) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	4	-	1	11.9	13.4	-	0.03m <sup>3</sup>
46		AS30151-C	E-Series - Anis - Floodlight Mounted with bracket with lens <b>200watt 3000K</b> - CRI 80 15778Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W408 x L280 x H40mm</b> Transparent / PC (Lens) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	3	-	1	11.2	12.6	-	0.0257m <sup>3</sup>
47		AS30153-C	E-Series - Anis - Floodlight Mounted with bracket with lens <b>300watt 3000K</b> - CRI 80 23636Lumen - 0.9PF 176 To 265V IP 65 - <b>Rectangular W473 x L335 x H45mm</b> Transparent / PC (Lens) - White / Aluminum (Housing) - <b>3 Year Warranty</b> Certified CB	2	-	1	11.9	13.4	-	0.03m <sup>3</sup>
48		EQ0743	AA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/500mA, with 4in1 cable, 1.5V, 1460mAh, 2220mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60°C, Weight 16g, D14xH50mm.	113	-	1	9.9	11.3	-	0.0293m <sup>3</sup>

Stamp



84753916

Signature

#	Container Number	Item Number	Item	Quantity	QTY/CTN	CTN	Total NW	Total GW	Unit Volume	Total Volume
49	020931 40HQ	EQ0744	AA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/500mA, with 4in1 cable, 1.5V, 1700mAh, 2600mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60°C, Weight 18g, D14xH50mm.	113	-	1	9.7	11.1	-	0.0356m <sup>3</sup>
50		EQ0746	AA Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 1460mAh, 2220mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60°C, Weight 16g, D14xH50mm.	113	-	1	5.8	7.3	-	0.0293m <sup>3</sup>
51		EQ0747	AA Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 1700mAh, 2600mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60°C, Weight 18g, D14xH50mm.	113	-	1	5.7	7.2	-	0.0293m <sup>3</sup>
52		EQ0748	AAA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/120mA, with 4in1 cable, 1.5V, 440mAh, 660mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature -20° / +60°C, Weight 8g, D10xH44mm.	153	-	1	7.9	9.3	-	0.0293m <sup>3</sup>
53		EQ0749	AAA Rechargeable batteries set/4, lithium-ion, Type-C charging 5VDC/250mA, with 4in1 cable, 1.5V, 580mAh, 880mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature -20° / +60°C, Weight 8.5g, D10xH44mm.	153	-	1	8.2	9.6	-	0.0293m <sup>3</sup>
54		EQ0750	AAA Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/120mA, with 2in1 cable, 1.5V, 440mAh, 660mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature -20° / +60°C, Weight 8g, D10xH44mm.	153	-	1	5.1	6.5	-	0.0293m <sup>3</sup>
55		EQ0751	AAA Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/250mA, with 2in1 cable, 1.5V, 580mAh, 880mWh, charging time 1-2h, long life ≥1000 cycles, max discharge current 1.5A, 1 year warranty, Operating temperature -20° / +60°C, Weight 8.5g, D10xH44mm.	153	-	1	5.4	6.8	-	0.0293m <sup>3</sup>
56		EQ0752	D type Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 4900mAh, 7400mWh, charging time~ 5h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60°C, Weight 80.5g, D32xH61mm.	43	-	1	6.6	8	-	0.0293m <sup>3</sup>
57		EQ0753	C type Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/500mA, with 2in1 cable, 1.5V, 4900mAh, 7400mWh, charging time~ 5h, long life ≥1000 cycles, max discharge current 2A, 1 year warranty, Operating temperature -20° / +60°C, Weight 55.5g, D25.2xH50.5mm.	53	-	1	6.6	8	-	0.0293m <sup>3</sup>
58		EQ0754	18650 Rechargeable battery, lithium-ion, Type-C charging 5VDC/700mA, with charging cable, 3.7V, 2000mAh, 7400mWh, charging time 3-3.5h, long life ≥1000 cycles, max discharge current 5A, 1 year warranty, Operating temperature -20° / +60°C, Weight 40g, D18xH65mm.	83	-	1	5.1	6.5	-	0.0293m <sup>3</sup>
59		EQ0755	16340 Rechargeable batteries set/2, lithium-ion, Type-C charging 5VDC/320mA, with 2in1 cable, 3.7V, 700mAh, 2500mWh, charging time 2-2.5h, long life ≥1000 cycles, max discharge current 3A, 1 year warranty, Operating temperature -20° / +60°C, Weight 19g, D16xH35mm.	93	-	1	5.1	6.5	-	0.0293m <sup>3</sup>
60		EQ0756	9V Rechargeable battery, lithium-ion, Type-C charging 5VDC/500mA, with charging cable, 9V, 400mAh, 3700mWh, charging time 2-2.5h, long life ≥1000 cycles, max discharge current 150mA, 1 year warranty, Operating temperature -20° / +60°C, Weight 24g, 48.1*26*16.8mm	83	-	1	3.3	4.7	-	0.0293m <sup>3</sup>
61		EQ0702	Collapsed mosquito trap, Built-in 2000mAh li battery UV wave length: 0.06W 360-400nm, 0.1W 2835 390-400nm, Grid voltage ≥2000V Size: 290*200*80mm Material: ABS+PC Working time after full charge : about 12 hours	3	-	1	2.86	3.69	-	0.0203m <sup>3</sup>
<b>Total</b>				<b>19,187</b>		<b>1,494</b>	<b>20,459</b>	<b>22,988</b>		<b>70.0371m<sup>3</sup></b>

Stamp



84753916

Signature