

## Packing List

**Consignee:** Tatawar Maana Est  
**Attention:** Abdulaziz aljouai  
**Tel:** +966504881194  
**Address:** KILO-08, Buraydah, Buraydah, Saudi Arabia

**From:** ATC MIDDLE EAST FZCO  
**Attention:** Echo Chan  
**Tel:** 008615018796671  
**Address:** JAFZA One, 11th Floor, Jebel Ali Free  
Zone , Dubai, UAE

**Shipment Number:** SH-010711250246  
**Order Number:** 0191,0280  
**Date:** 17/11/2025

Stamp



23091765

Signature

| #  | Container Number | Item Number | Item                                                                                                                                                                                                                                                                                      | Quantity | QTY/CTN | CTN  | Total NW | Total GW | Unit Volume | Total Volume          |
|----|------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------|------|----------|----------|-------------|-----------------------|
| 1  | 024631<br>40HQ   | RI30694-A   | E-Series - Rami - Street Light Mounted on pole <b>Dimmable 1-10V 200watt 3000K</b> - CRI 70 26000Lumen - 0.95PF 100 To 277V IP 66 - <b>LUMILEDS LED Rectangular W255 x L628 x H89mm</b> Black / Die-cast aluminum (Housing) - <b>5 Year Warranty</b> Certified CB                         | 20       | 1       | 20   | 83       | 104      | 0.0191      | 0.3827 m <sup>3</sup> |
| 2  |                  | RI40695-A   | E-Series - Rami - Street Light Mounted on pole <b>Dimmable 1-10V 200watt 4000K</b> - CRI 70 26000Lumen - 0.95PF 100 To 277V IP 66 - <b>LUMILEDS LED Rectangular W255 x L628 x H89mm</b> Black / Die-cast aluminum (Housing) - <b>5 Year Warranty</b> Certified CB                         | 1,000    | 1       | 1000 | 4150     | 5200     | 0.0191      | 19.136 m <sup>3</sup> |
| 3  |                  | RI60696-A   | E-Series - Rami - Street Light Mounted on pole <b>Dimmable 1-10V 200watt 6000K</b> - CRI 70 26000Lumen - 0.95PF 100 To 277V IP 66 - <b>LUMILEDS LED Rectangular W255 x L628 x H89mm</b> Black / Die-cast aluminum (Housing) - <b>5 Year Warranty</b> Certified CB                         | 117      | 1       | 117  | 485.55   | 608.4    | 0.0191      | 2.2389 m <sup>3</sup> |
| 4  |                  | TA20780-A   | E-Series - Taj - Strip light Surface 2835SMD 120Pcs/1M single line 10Cm/cut <b>9watt/m 2700K</b> - CRI 80 670Lumen/m - 0.9PF <b>220 To 240V</b> IP 65 - <b>Linear W10.5 x L50000 x H4mm</b> Cut Out 100mm Transparent / Copper + PVC (Body) - 1900g - <b>3 Year Warranty</b> Certified CB | 1,000    | 1       | 1000 | 2800     | 3400     | 0.0088      | 8.788 m <sup>3</sup>  |
| 5  |                  | TA30781-A   | E-Series - Taj - Strip light Surface 2835SMD 120Pcs/1M single line 10Cm/cut <b>9watt/m 3000K</b> - CRI 80 670Lumen/m - 0.9PF <b>220 To 240V</b> IP 65 - <b>Linear W10.5 x L50000 x H4mm</b> Cut Out 100mm Transparent / Copper + PVC (Body) - 1900g - <b>3 Year Warranty</b> Certified CB | 1,100    | 1       | 1100 | 3080     | 3740     | 0.0088      | 9.6668 m <sup>3</sup> |
| 6  |                  | TA40782-A   | E-Series - Taj - Strip light Surface 2835SMD 120Pcs/1M single line 10Cm/cut <b>9watt/m 4000K</b> - CRI 80 670Lumen/m - 0.9PF <b>220 To 240V</b> IP 65 - <b>Linear W10.5 x L50000 x H4mm</b> Cut Out 100mm Transparent / Copper + PVC (Body) - 1900g - <b>3 Year Warranty</b> Certified CB | 1,000    | 1       | 1000 | 2800     | 3400     | 0.0088      | 8.788 m <sup>3</sup>  |
| 7  |                  | TA60783-A   | E-Series - Taj - Strip light Surface 2835SMD 120Pcs/1M single line 10Cm/cut <b>9watt/m 6000K</b> - CRI 80 670Lumen/m - 0.9PF <b>220 To 240V</b> IP 65 - <b>Linear W10.5 x L50000 x H4mm</b> Cut Out 100mm Transparent / Copper + PVC (Body) - 1900g - <b>3 Year Warranty</b> Certified CB | 200      | 1       | 200  | 560      | 680      | 0.0088      | 1.7576 m <sup>3</sup> |
| 8  |                  | TL20754-A   | E-Series - Tala - Strip light Surface 2835SMD 60Pcs/1M/ single line 10Cm/cut <b>5watt/m 2700K</b> - CRI 80 540Lumen/m - 1PF <b>24V</b> IP 20 - <b>Linear W8 x L5000 x H1.28mm</b> Transparent / copper (Housing) - <b>3 Year Warranty</b> Certified CB                                    | 300      | 50      | 6    | 31.2     | 34.8     | 0.0379      | 0.2274 m <sup>3</sup> |
| 9  |                  | TL20755-A   | E-Series - Tala - Strip light Surface 2835SMD 60Pcs/1M/ single line 10Cm/cut <b>5watt/m 2700K</b> - CRI 80 350Lumen/m - 1PF <b>24V</b> IP 65 - <b>Linear W10 x L5000 x H4mm</b> Cut Out 100mm Transparent / Copper + Silicone (Body) - <b>3 Year Warranty</b> Certified CB                | 300      | 50      | 6    | 31.2     | 34.8     | 0.0379      | 0.2274 m <sup>3</sup> |
| 10 |                  | TL30463-B   | E-Series - Tala - Strip light Surface 2835SMD 60Pcs/1M/ single line 10Cm/cut <b>5watt/m 3000K</b> - CRI 80 540Lumen/m - 1PF <b>24V</b> IP 20 - <b>Linear W8 x L5000 x H1.28mm</b> Transparent / copper (Body) - <b>3 Year Warranty</b> Certified CB                                       | 300      | 50      | 6    | 31.2     | 34.8     | 0.0379      | 0.2274 m <sup>3</sup> |
| 11 |                  | TL30475-B   | E-Series - Tala - Strip light Surface 2835SMD 60Pcs/1M/ single line 10Cm/cut <b>5watt/m 3000K</b> - CRI 80 350Lumen/m - 1PF <b>24V</b> IP 65 - <b>Linear W10 x L5000 x H4mm</b> Transparent / Copper + Silicone (Body) - <b>3 Year Warranty</b> Certified CB                              | 300      | 50      | 6    | 31.2     | 34.8     | 0.0379      | 0.2274 m <sup>3</sup> |
| 12 |                  | TL40464-B   | E-Series - Tala - Strip light Surface 2835SMD 60Pcs/1M/ single line 10Cm/cut <b>5watt/m 4000K</b> - CRI 80 540Lumen/m - 1PF <b>24V</b> IP 20 - <b>Linear W8 x L5000 x H1.28mm</b> Transparent / copper (Body) - <b>3 Year Warranty</b> Certified CB                                       | 300      | 50      | 6    | 31.2     | 34.8     | 0.0379      | 0.2274 m <sup>3</sup> |
| 13 |                  | TL40476-B   | E-Series - Tala - Strip light Surface 2835SMD 60Pcs/1M/ single line 10Cm/cut <b>5watt/m 4000K</b> - CRI 80 350Lumen/m - 1PF <b>24V</b> IP 65 - <b>Linear W10 x L5000 x H4mm</b> Transparent / Copper + Silicone (Body) - <b>3 Year Warranty</b> Certified CB                              | 300      | 50      | 6    | 31.2     | 34.8     | 0.0379      | 0.2274 m <sup>3</sup> |
| 14 |                  | TL20756-A   | E-Series - Tala - Strip light Surface 2835SMD 120Pcs/1M single line 5Cm/cut <b>11watt/m 2700K</b> - CRI 80 1100Lumen/m - 1PF <b>24V</b> IP 20 - <b>Linear W8 x L5000 x H1.28mm</b> Transparent / copper (Body) - <b>3 Year Warranty</b> Certified CB                                      | 200      | 50      | 4    | 20.8     | 23.2     | 0.0379      | 0.1516 m <sup>3</sup> |

Stamp



23091765

2 of 4

Powered By LUMYTIC

Signature

| #  | Container Number | Item Number | Item                                                                                                                                                                                                                                                               | Quantity | QTY/CTN | CTN | Total NW | Total GW | Unit Volume | Total Volume          |
|----|------------------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------|-----|----------|----------|-------------|-----------------------|
| 15 | 024631<br>40HQ   | TL20757-A   | E-Series – Tala – Strip light Surface 2835SMD 120Pcs/1M single line<br>5Cm/cut <b>11watt/m 2700K</b> – CRI 80 900Lumen/m – 1PF <b>24V</b> IP 65 – <b>Linear W10 x L5000 x H4mm</b> Transparent / Copper + Silicone (Body) – <b>3 Year Warranty</b> Certified CB    | 200      | 50      | 4   | 20.8     | 23.2     | 0.0379      | 0.1516 m <sup>3</sup> |
| 16 |                  | TL30466-B   | E-Series – Tala – Strip light Surface 2835SMD 120Pcs/1M single line<br>5Cm/cut <b>11watt/m 3000K</b> – CRI 80 1100Lumen/m – 1PF <b>24V</b> IP 20 – <b>Linear W8 x L5000 x H1.28mm</b> Transparent / copper (Body) – <b>3 Year Warranty</b> Certified CB            | 800      | 50      | 16  | 83.2     | 92.8     | 0.0379      | 0.6065 m <sup>3</sup> |
| 17 |                  | TL30478-B   | E-Series – Tala – Strip light Surface 2835SMD 120Pcs/1M single line<br>5Cm/cut <b>11watt/m 3000K</b> – CRI 80 900Lumen/m – 1PF <b>24V</b> IP 65 – <b>Linear W10 x L5000 x H4mm</b> Transparent / Copper + Silicone (Body) – <b>3 Year Warranty</b> Certified CB    | 500      | 50      | 10  | 52       | 58       | 0.0379      | 0.379 m <sup>3</sup>  |
| 18 |                  | TL40467-B   | E-Series – Tala – Strip light Surface 2835SMD 120Pcs/1M single line<br>5Cm/cut <b>11watt/m 4000K</b> – CRI 80 1100Lumen/m – 1PF <b>24V</b> IP 20 – <b>Linear W8 x L5000 x H1.28mm</b> Transparent / copper (Body) – <b>3 Year Warranty</b> Certified CB            | 500      | 50      | 10  | 52       | 58       | 0.0379      | 0.379 m <sup>3</sup>  |
| 19 |                  | TL40479-B   | E-Series – Tala – Strip light Surface 2835SMD 120Pcs/1M single line<br>5Cm/cut <b>11watt/m 4000K</b> – CRI 80 900Lumen/m – 1PF <b>24V</b> IP 65 – <b>Linear W10 x L5000 x H4mm</b> Transparent / Copper + Silicone (Body) – <b>3 Year Warranty</b> Certified CB    | 300      | 50      | 6   | 31.2     | 34.8     | 0.0379      | 0.2274 m <sup>3</sup> |
| 20 |                  | TL20760-A   | E-Series – Tala – Strip light Surface 2835SMD 240Pcs/1M single line<br>2.5Cm/cut <b>18watt/m 2700K</b> – CRI 80 1800Lumen/m – 1PF <b>24V</b> IP 20 – <b>Linear W10 x L5000 x H1.28mm</b> Transparent / copper (Body) – <b>3 Year Warranty</b> Certified CB         | 100      | 50      | 2   | 24.2     | 25.4     | 0.0504      | 0.1009 m <sup>3</sup> |
| 21 |                  | TL30469-B   | E-Series – Tala – Strip light Surface 2835SMD 180Pcs/1M single line<br>3.3Cm/cut <b>16watt/m 3000K</b> – CRI 80 1600Lumen/m – 1PF <b>24V</b> IP 20 – <b>Linear W10 x L5000 x H1.28mm</b> Transparent / copper (Body) – <b>3 Year Warranty</b> Certified CB         | 500      | 50      | 10  | 121      | 127      | 0.0504      | 0.5044 m <sup>3</sup> |
| 22 |                  | TL30481-B   | E-Series – Tala – Strip light Surface 2835SMD 180Pcs/1M single line<br>3.3Cm/cut <b>16watt/m 3000K</b> – CRI 80 1500Lumen/m – 1PF <b>24V</b> IP 65 – <b>Linear W12 x L5000 x H4mm</b> Transparent / Copper + Silicone (Body) – <b>3 Year Warranty</b> Certified CB | 300      | 50      | 6   | 72.6     | 76.2     | 0.0504      | 0.3026 m <sup>3</sup> |
| 23 |                  | TL40482-B   | E-Series – Tala – Strip light Surface 2835SMD 180Pcs/1M single line<br>3.3Cm/cut <b>16watt/m 4000K</b> – CRI 80 1500Lumen/m – 1PF <b>24V</b> IP 65 – <b>Linear W12 x L5000 x H4mm</b> Transparent / Copper + Silicone (Body) – <b>3 Year Warranty</b> Certified CB | 500      | 50      | 10  | 121      | 127      | 0.0504      | 0.5044 m <sup>3</sup> |
| 24 |                  | TL30472-B   | E-Series – Tala – Strip light Surface 2835SMD 240Pcs/1M single line<br>2.5Cm/cut <b>18watt/m 3000K</b> – CRI 80 1800Lumen/m – 1PF <b>24V</b> IP 20 – <b>Linear W10 x L5000 x H1.28mm</b> Transparent / copper (Body) – <b>3 Year Warranty</b> Certified CB         | 100      | 50      | 2   | 24.2     | 25.4     | 0.0504      | 0.1009 m <sup>3</sup> |
| 25 |                  | TL20758-A   | E-Series – Tala – Strip light Surface 2835SMD 180Pcs/1M single line<br>3.3Cm/cut <b>16watt/m 2700K</b> – CRI 80 1600Lumen/m – 1PF <b>24V</b> IP 20 – <b>Linear W10 x L5000 x H1.28mm</b> Transparent / copper (Body) – <b>3 Year Warranty</b> Certified CB         | 300      | 50      | 6   | 72.6     | 76.2     | 0.0504      | 0.3026 m <sup>3</sup> |
| 26 |                  | TL20759-A   | E-Series – Tala – Strip light Surface 2835SMD 180Pcs/1M single line<br>3.3Cm/cut <b>16watt/m 2700K</b> – CRI 80 1500Lumen/m – 1PF <b>24V</b> IP 65 – <b>Linear W12 x L5000 x H4mm</b> Transparent / Copper + Silicone (Body) – <b>3 Year Warranty</b> Certified CB | 200      | 50      | 4   | 48.4     | 50.8     | 0.0504      | 0.2018 m <sup>3</sup> |
| 27 |                  | TL40470-B   | E-Series – Tala – Strip light Surface 2835SMD 180Pcs/1M single line<br>3.3Cm/cut <b>16watt/m 4000K</b> – CRI 80 1600Lumen/m – 1PF <b>24V</b> IP 20 – <b>Linear W10 x L5000 x H1.28mm</b> Transparent / copper (Body) – <b>3 Year Warranty</b> Certified CB         | 300      | 50      | 6   | 72.6     | 76.2     | 0.0504      | 0.3026 m <sup>3</sup> |
| 28 |                  | TL40473-B   | E-Series – Tala – Strip light Surface 2835SMD 240Pcs/1M single line<br>2.5Cm/cut <b>18watt/m 4000K</b> – CRI 80 1800Lumen/m – 1PF <b>24V</b> IP 20 – <b>Linear W10 x L5000 x H1.28mm</b> Transparent / copper (Body) – <b>3 Year Warranty</b> Certified CB         | 200      | 50      | 4   | 48.4     | 50.8     | 0.0504      | 0.2018 m <sup>3</sup> |
| 29 |                  | ES-0897A    | Rafeed, Tri-proof Housing IP65, 9W for T8 DOUBLE-END wiring ABS base, PC cover, with stainless steel clips, T8 lamp holder (UL), without LED tube, Dimensions: 670x68x73 mm, warranty 5years<br>Certified CB                                                       | 280      | 20      | 14  | 144.2    | 168      | 0.0631      | 0.8835 m <sup>3</sup> |
| 30 |                  | ES-0896A    | Rafeed, Tri-proof Housing IP65, 2*9W for T8 DOUBLE-END wiring ABS base, PC cover, with stainless steel clips, T8 lamp holder (UL), without LED tube, Dimensions: 670x104x73 mm, warranty 5years<br>Certified CB                                                    | 285      | 15      | 19  | 210.9    | 241.3    | 0.0707      | 1.3437 m <sup>3</sup> |
| 31 |                  | ES-0898A    | Rafeed, Tri-proof Housing IP65, 18W for T8 DOUBLE-END wiring ABS base, PC cover, with stainless steel clips, T8 lamp holder (UL), without LED tube, Dimensions: 1270x68x73mm, warranty 5years<br>Certified CB                                                      | 588      | 12      | 49  | 568.4    | 651.7    | 0.0721      | 3.535 m <sup>3</sup>  |

Stamp



23091765

3 of 4

Powered By LUMYTIC

Signature

| #     | Container Number | Item Number                                    | Item                                                                                                                                                                                                                                                              | Quantity | QTY/CTN | CTN   | Total NW | Total GW | Unit Volume | Total Volume |
|-------|------------------|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------|-------|----------|----------|-------------|--------------|
| 32    | 024631<br>40HQ   | ES-0899A                                       | Rafeed, Tri-proof Housing IP65, 2*18W for T8 DOUBLE-END wiring ABS base, PC cover, with stainless steel clips, T8 lamp holder (UL), without LED tube, Dimensions: 1270x104x73mm, warranty 5years<br>Certified CB                                                  | 990      | 10      | 99    | 1237.5   | 1405.8   | 0.088       | 8.7098 m³    |
| 33    |                  | D0117 - SS-150VH-A215B<br>Driver for RI30691-A | E-Series - Rami - Street Light Mounted on pole <b>Dimmable 1-10V 150watt 3000K</b> - CRI 70 19500Lumen - 0.95PF 100 To 277V IP 66 - <b>LUMILEDS LED Rectangular W234 x L576 x H89mm</b> Black / Die-cast aluminum (Housing) - <b>5 Year Warranty</b> Certified CB | 14       | -       | 1     | 9        | 10       | -           | 0.0264 m³    |
| 34    |                  | D0117 - SS-150VH-A215B<br>Driver for RI30691-A | E-Series - Rami - Street Light Mounted on pole <b>Dimmable 1-10V 150watt 3000K</b> - CRI 70 19500Lumen - 0.95PF 100 To 277V IP 66 - <b>LUMILEDS LED Rectangular W234 x L576 x H89mm</b> Black / Die-cast aluminum (Housing) - <b>5 Year Warranty</b> Certified CB | 1        | -       | 1     | 9        | 10       | -           | 0.0264 m³    |
| 35    |                  | D0117 - SS-150VH-A215B<br>Driver for RI40692-A | E-Series - Rami - Street Light Mounted on pole <b>Dimmable 1-10V 150watt 4000K</b> - CRI 70 19500Lumen - 0.95PF 100 To 277V IP 66 - <b>LUMILEDS LED Rectangular W234 x L576 x H89mm</b> Black / Die-cast aluminum (Housing) - <b>5 Year Warranty</b> Certified CB | 9        |         |       |          |          |             |              |
| 36    |                  | D0117 - SS-150VH-A215B<br>Driver for RI60693-A | E-Series - Rami - Street Light Mounted on pole <b>Dimmable 1-10V 150watt 6000K</b> - CRI 70 19500Lumen - 0.95PF 100 To 277V IP 66 - <b>LUMILEDS LED Rectangular W234 x L576 x H89mm</b> Black / Die-cast aluminum (Housing) - <b>5 Year Warranty</b> Certified CB | 4        |         |       |          |          |             |              |
| 37    |                  | D0118 - SS-200VH-A286B<br>Driver for RI30694-A | E-Series - Rami - Street Light Mounted on pole <b>Dimmable 1-10V 200watt 3000K</b> - CRI 70 26000Lumen - 0.95PF 100 To 277V IP 66 - <b>LUMILEDS LED Rectangular W255 x L628 x H89mm</b> Black / Die-cast aluminum (Housing) - <b>5 Year Warranty</b> Certified CB | 14       | -       | 1     | 12       | 13.5     | -           | 0.0264 m³    |
| 38    |                  | D0117 - SS-150VH-A215B<br>Driver for RI60693-A | E-Series - Rami - Street Light Mounted on pole <b>Dimmable 1-10V 150watt 6000K</b> - CRI 70 19500Lumen - 0.95PF 100 To 277V IP 66 - <b>LUMILEDS LED Rectangular W234 x L576 x H89mm</b> Black / Die-cast aluminum (Housing) - <b>5 Year Warranty</b> Certified CB | 2        | -       | 1     | 10       | 11       | -           | 0.0211 m³    |
| 39    |                  | D0118 - SS-200VH-A286B<br>Driver for RI30694-A | E-Series - Rami - Street Light Mounted on pole <b>Dimmable 1-10V 200watt 3000K</b> - CRI 70 26000Lumen - 0.95PF 100 To 277V IP 66 - <b>LUMILEDS LED Rectangular W255 x L628 x H89mm</b> Black / Die-cast aluminum (Housing) - <b>5 Year Warranty</b> Certified CB | 1        |         |       |          |          |             |              |
| 40    |                  | D0118 - SS-200VH-A286B<br>Driver for RI40695-A | E-Series - Rami - Street Light Mounted on pole <b>Dimmable 1-10V 200watt 4000K</b> - CRI 70 26000Lumen - 0.95PF 100 To 277V IP 66 - <b>LUMILEDS LED Rectangular W255 x L628 x H89mm</b> Black / Die-cast aluminum (Housing) - <b>5 Year Warranty</b> Certified CB | 7        |         |       |          |          |             |              |
| Total |                  |                                                |                                                                                                                                                                                                                                                                   | 13,432   |         | 4,758 | 17,212   | 20,778   |             | 71.112 m³    |

Stamp



23091765

4 of 4

Powered By LUMYTIC

Signature