

Cree® XLamp® MHB-A LEDs



PRODUCT DESCRIPTION

The XLamp® MHB-A LED is a new generation of high-power LED that delivers a more effective way to achieve low-cost systems than mid-power (MP) LEDs. Built using Cree’s high-reliability ceramic-package technology, the XLamp MHB-A LED is able to operate at higher temperatures than MP LEDs with no reduction in rated lifetime, enabling an impressive 60% reduction in heat sink size and cost. Using up to 26 times fewer LEDs than MP LEDs to achieve the same performance, the XLamp MHB-A LED is optimized to simplify LED system designs for directional and semi-directional applications.

FEATURES

- Flexible 9-V, 18-V or 36-V options
- Maximum drive current: 700 mA (9 V), 350 mA (18 V), 175 mA (36 V)
- Viewing angle: 115°
- Available in 70-CRI, 80-CRI and 90-CRI options
- Unlimited floor life at $\leq 30\text{ }^{\circ}\text{C}/85\%\text{ RH}$
- Reflow solderable - JEDEC J-STD-020C
- Electrically neutral thermal path
- RoHS-compliant
- UL® recognized component (E349212)



TABLE OF CONTENTS

Characteristics	2
Flux Characteristics, EasyWhite®	
Order Codes and Bins - 9 V.....	3
Flux Characteristics, EasyWhite®	
Order Codes and Bins - 18 V.....	5
Flux Characteristics, EasyWhite®	
Order Codes and Bins - 36 V.....	7
Relative Spectral Power Distribution ..	9
Relative Flux vs. Junction Temperature	9
Electrical Characteristics	10
Relative Flux vs. Current	11
Relative Chromaticity vs. Current.....	13
Relative Chromaticity vs. Temperature	14
Typical Spatial Distribution.....	15
Thermal Design.....	15
Performance Groups – Luminous Flux.....	17
Performance Groups – Chromaticity .	17
Cree’s Standard White Chromaticity Regions Plotted on the 1931 CIE Curve	18
Bin and Order Code Format.....	19
Reflow Soldering Characteristics	20
Notes.....	21
Mechanical Dimensions.....	22
Tape and Reel	23
Packaging.....	24

CHARACTERISTICS

Characteristics	Unit	Minimum	Typical	Maximum
Thermal resistance, junction to solder point	°C/W		5.5	
Viewing angle (FWHM)	degrees		115	
Temperature coefficient of voltage (9 V)	mV/°C		-4	
Temperature coefficient of voltage (18 V)	mV/°C		-8	
Temperature coefficient of voltage (36 V)	mV/°C		-16	
ESD withstand voltage (HBM per Mil-Std-883D)	V			8000
DC forward current (9 V)	mA		480	700
DC forward current (18 V)	mA		240	350
DC forward current (36 V)	mA		120	175
Reverse current (9 V, 18 V, 36 V)	mA			0.1
Forward voltage (9 V, @ 480 mA, 85 °C)	V		9.25	
Forward voltage (9 V, @ 480 mA, 25 °C)	V			10.5
Forward voltage (18 V, @ 240 mA, 85 °C)	V		18.5	
Forward voltage (18 V, @ 240 mA, 25 °C)	V			21
Forward voltage (36 V, @ 120 mA, 85 °C)	V		37	
Forward voltage (36 V, @ 120 mA, 25 °C)	V			42
LED junction temperature	°C			150

FLUX CHARACTERISTICS, EASYWHITE® ORDER CODES AND BINS - 9 V

The following table provides order codes for XLamp MHB-A LEDs. For a complete description of the order code nomenclature, please see the Bin and Order Code Formats section (page 19).

Test condition: $T_j = 85\text{ }^\circ\text{C}$, 9 V, $I_f = 480\text{ mA}$

Nominal CCT	CRI	Minimum Luminous Flux		2-Step		3-Step		5-Step	
	Min	Group	Flux (lm)	Group	Order Code	Group	Order Code	Group	Order Code
6500 K	70	D2	510					65E	MHBAWT-0000-000C0BD265E
		D4	550						MHBAWT-0000-000C0BD465E
	80	C4	475					65E	MHBAWT-0000-000C0HC465E
		D2	510						MHBAWT-0000-000C0HD265E
	90	B4	410					65E	MHBAWT-0000-000C0UB465E
		C2	440						MHBAWT-0000-000C0UC265E
5700 K	70	D2	510					57E	MHBAWT-0000-000C0BD257E
		D4	550						MHBAWT-0000-000C0BD457E
	80	C4	475					57E	MHBAWT-0000-000C0HC457E
		D2	510						MHBAWT-0000-000C0HD257E
	90	B4	410					57E	MHBAWT-0000-000C0UB457E
		C2	440						MHBAWT-0000-000C0UC257E
5000 K	70	D2	510					50E	MHBAWT-0000-000C0BD250E
		D4	550						MHBAWT-0000-000C0BD450E
	80	C4	475			50G	MHBAWT-0000-000C0HC450G	50E	MHBAWT-0000-000C0HC450E
		D2	510				MHBAWT-0000-000C0HD250G		MHBAWT-0000-000C0HD250E
	90	B4	410			50G	MHBAWT-0000-000C0UB450G	50E	MHBAWT-0000-000C0UB450E
		C2	440				MHBAWT-0000-000C0UC250G		MHBAWT-0000-000C0UC250E

Notes

- Cree maintains a tolerance of $\pm 7\%$ on flux and power measurements, ± 0.005 on chromaticity (CCx, CCy) measurements and a tolerance of ± 2 on CRI measurements. See the Measurements section (page 21).
- Cree XLamp MHB-A LED order codes specify only a minimum flux bin and not a maximum. Cree may ship reels in flux bins higher than the minimum specified by the order code without advance notice. Shipments will always adhere to the chromaticity bin restrictions specified by the order code.

FLUX CHARACTERISTICS, EASYWHITE® ORDER CODES AND BINS - 9 V - CONTINUED

Nominal CCT	CRI	Minimum Luminous Flux		2-Step		3-Step		5-Step	
	Min	Group	Flux (lm)	Group	Order Code	Group	Order Code	Group	Order Code
4000 K	70	C4	475					40E	MHBAWT-0000-000C0BC440E
		D2	510				MHBAWT-0000-000C0BD240E		
		D4	550				MHBAWT-0000-000C0BD440E		
	80	C4	475	40H	MHBAWT-0000-000C0HC440H	40G	MHBAWT-0000-000C0HC440G		
		D2	510		MHBAWT-0000-000C0HD240H		MHBAWT-0000-000C0HD240G		
	90	B2	380	40H	MHBAWT-0000-000C0UB240H	40G	MHBAWT-0000-000C0UB240G		
B4		410	MHBAWT-0000-000C0UB440H		MHBAWT-0000-000C0UB440G				
3500 K	80	C4	475	35H	MHBAWT-0000-000N0HC435H	35G	MHBAWT-0000-000N0HC435G		
		D2	510		MHBAWT-0000-000N0HD235H		MHBAWT-0000-000N0HD235G		
	90	A2	330	35H	MHBAWT-0000-000C0UA235H	35G	MHBAWT-0000-000C0UA235G		
		A4	355		MHBAWT-0000-000C0UA435H		MHBAWT-0000-000C0UA435G		
3000 K	80	C2	440	30H	MHBAWT-0000-000C0HC230H	30G	MHBAWT-0000-000C0HC230G		
		C4	475		MHBAWT-0000-000C0HC430H		MHBAWT-0000-000C0HC430G		
	90	A2	330	30H	MHBAWT-0000-000C0UA230H	30G	MHBAWT-0000-000C0UA230G		
		A4	355		MHBAWT-0000-000C0UA430H		MHBAWT-0000-000C0UA430G		
2700 K	80	C2	440	27H	MHBAWT-0000-000C0HC227H	27G	MHBAWT-0000-000C0HC227G		
		C4	475		MHBAWT-0000-000C0HC427H		MHBAWT-0000-000C0HC427G		
	90	A2	330	27H	MHBAWT-0000-000C0UA227H	27G	MHBAWT-0000-000C0UA227G		
		A4	355		MHBAWT-0000-000C0UA427H		MHBAWT-0000-000C0UA427G		

Notes

- Cree maintains a tolerance of $\pm 7\%$ on flux and power measurements, ± 0.005 on chromaticity (CCx, CCy) measurements and a tolerance of ± 2 on CRI measurements. See the Measurements section (page 21).
- Cree XLamp MHB-A LED order codes specify only a minimum flux bin and not a maximum. Cree may ship reels in flux bins higher than the minimum specified by the order code without advance notice. Shipments will always adhere to the chromaticity bin restrictions specified by the order code.

FLUX CHARACTERISTICS, EASYWHITE® ORDER CODES AND BINS - 18 V

The following table provides order codes for XLamp MHB-A LEDs. For a complete description of the order code nomenclature, please see the Bin and Order Code Formats section (page 19).

Test condition: $T_j = 85\text{ }^\circ\text{C}$, 18 V, $I_f = 240\text{ mA}$

Nominal CCT	CRI	Minimum Luminous Flux		2-Step		3-Step		5-Step	
	Min	Group	Flux (lm)	Group	Order Code	Group	Order Code	Group	Order Code
6500 K	70	D2	510					65E	MHBAWT-0000-000F0BD265E
		D4	550						MHBAWT-0000-000F0BD465E
	80	C4	475					65E	MHBAWT-0000-000F0HC465E
		D2	510						MHBAWT-0000-000F0HD265E
	90	B4	410					65E	MHBAWT-0000-000F0UB465E
		C2	440						MHBAWT-0000-000F0UC265E
5700 K	70	D2	510					57E	MHBAWT-0000-000F0BD257E
		D4	550						MHBAWT-0000-000F0BD457E
	80	C4	475					57E	MHBAWT-0000-000F0HC457E
		D2	510						MHBAWT-0000-000F0HD257E
	90	B4	410					57E	MHBAWT-0000-000F0UB457E
		C2	440						MHBAWT-0000-000F0UC257E
5000 K	70	D2	510					50E	MHBAWT-0000-000F0BD250E
		D4	550						MHBAWT-0000-000F0BD450E
	80	C4	475				50G	50E	MHBAWT-0000-000F0HC450G
		D2	510						MHBAWT-0000-000F0HD250G
	90	B4	410				50G	50E	MHBAWT-0000-000F0UB450G
		C2	440						MHBAWT-0000-000F0UC250G

Notes

- Cree maintains a tolerance of $\pm 7\%$ on flux and power measurements, ± 0.005 on chromaticity (CCx, CCy) measurements and a tolerance of ± 2 on CRI measurements. See the Measurements section (page 21).
- Cree XLamp MHB-A LED order codes specify only a minimum flux bin and not a maximum. Cree may ship reels in flux bins higher than the minimum specified by the order code without advance notice. Shipments will always adhere to the chromaticity bin restrictions specified by the order code.

FLUX CHARACTERISTICS, EASYWHITE® ORDER CODES AND BINS - 18 V - CONTINUED

Nominal CCT	CRI	Minimum Luminous Flux		2-Step		3-Step		5-Step	
	Min	Group	Flux (lm)	Group	Order Code	Group	Order Code	Group	Order Code
4000 K	70	C4	475					40E	MHBAWT-0000-000F0BC440E
		D2	510						MHBAWT-0000-000F0BD240E
		D4	550						MHBAWT-0000-000F0BD440E
	80	C4	475	40H	MHBAWT-0000-000F0HC440H	40G	MHBAWT-0000-000F0HC440G		
		D2	510		MHBAWT-0000-000F0HD240H		MHBAWT-0000-000F0HD240G		
	90	B2	380	40H	MHBAWT-0000-000F0UB240H	40G	MHBAWT-0000-000F0UB240G		
B4		410	MHBAWT-0000-000F0UB440H		MHBAWT-0000-000F0UB440G				
3500 K	80	C4	475	35H	MHBAWT-0000-000F0HC435H	35G	MHBAWT-0000-000F0HC435G		
		D2	510		MHBAWT-0000-000F0HD235H		MHBAWT-0000-000F0HD235G		
	90	A2	330	35H	MHBAWT-0000-000F0UA235H	35G	MHBAWT-0000-000F0UA235G		
		A4	355		MHBAWT-0000-000F0UA435H		MHBAWT-0000-000F0UA435G		
3000 K	80	C2	440	30H	MHBAWT-0000-000F0HC230H	30G	MHBAWT-0000-000F0HC230G		
		C4	475		MHBAWT-0000-000F0HC430H		MHBAWT-0000-000F0HC430G		
	90	A2	330	30H	MHBAWT-0000-000F0UA230H	30G	MHBAWT-0000-000F0UA230G		
		A4	355		MHBAWT-0000-000F0UA430H		MHBAWT-0000-000F0UA430G		
2700 K	80	C2	440	27H	MHBAWT-0000-000F0HC227H	27G	MHBAWT-0000-000F0HC227G		
		C4	475		MHBAWT-0000-000F0HC427H		MHBAWT-0000-000F0HC427G		
	90	A2	330	27H	MHBAWT-0000-000F0UA227H	27G	MHBAWT-0000-000F0UA227G		
		A4	355		MHBAWT-0000-000F0UA427H		MHBAWT-0000-000F0UA427G		

Notes

- Cree maintains a tolerance of $\pm 7\%$ on flux and power measurements, ± 0.005 on chromaticity (CCx, CCy) measurements and a tolerance of ± 2 on CRI measurements. See the Measurements section (page 21).
- Cree XLamp MHB-A LED order codes specify only a minimum flux bin and not a maximum. Cree may ship reels in flux bins higher than the minimum specified by the order code without advance notice. Shipments will always adhere to the chromaticity bin restrictions specified by the order code.

FLUX CHARACTERISTICS, EASYWHITE® ORDER CODES AND BINS - 36 V

The following table provides order codes for XLamp MHB-A LEDs. For a complete description of the order code nomenclature, please see the Bin and Order Code Formats section (page 19).

Test condition: $T_j = 85\text{ }^\circ\text{C}$, 36 V, $I_f = 120\text{ mA}$

Nominal CCT	CRI	Minimum Luminous Flux		2-Step		3-Step		5-Step		
	Min	Group	Flux (lm)	Group	Order Code	Group	Order Code	Group	Order Code	
6500 K	70	D2	510					65E	MHBAWT-0000-000N0BD265E	
		D4	550						MHBAWT-0000-000N0BD465E	
	80	C4	475					65E	MHBAWT-0000-000N0HC465E	
		D2	510						MHBAWT-0000-000N0HD265E	
	90	B4	410					65E	MHBAWT-0000-000N0UB465E	
		C2	440						MHBAWT-0000-000N0UC265E	
5700 K	70	D2	510					57E	MHBAWT-0000-000N0BD257E	
		D4	550						MHBAWT-0000-000N0BD457E	
	80	C4	475					57E	MHBAWT-0000-000N0HC457E	
		D2	510						MHBAWT-0000-000N0HD257E	
	90	B4	410					57E	MHBAWT-0000-000N0UB457E	
		C2	440						MHBAWT-0000-000N0UC257E	
5000 K	70	D2	510					50E	MHBAWT-0000-000N0BD250E	
		D4	550						MHBAWT-0000-000N0BD450E	
	80	C4	475				50G	MHBAWT-0000-000N0HC450G	50E	MHBAWT-0000-000N0HC450E
		D2	510					MHBAWT-0000-000N0HD250G		MHBAWT-0000-000N0HD250E
	90	B4	410				50G	MHBAWT-0000-000N0UB450G	50E	MHBAWT-0000-000N0UB450E
		C2	440					MHBAWT-0000-000N0UC250G		MHBAWT-0000-000N0UC250E

Notes

- Cree maintains a tolerance of $\pm 7\%$ on flux and power measurements, ± 0.005 on chromaticity (CCx, CCy) measurements and a tolerance of ± 2 on CRI measurements. See the Measurements section (page 21).
- Cree XLamp MHB-A LED order codes specify only a minimum flux bin and not a maximum. Cree may ship reels in flux bins higher than the minimum specified by the order code without advance notice. Shipments will always adhere to the chromaticity bin restrictions specified by the order code.


FLUX CHARACTERISTICS, EASYWHITE® ORDER CODES AND BINS - 36 V - CONTINUED

Nominal CCT	CRI	Minimum Luminous Flux		2-Step		3-Step		5-Step	
	Min	Group	Flux (lm)	Group	Order Code	Group	Order Code	Group	Order Code
4000 K	70	C4	475					40E	MHBAWT-0000-000N0BC440E
		D2	510				MHBAWT-0000-000N0BD240E		
		D4	550				MHBAWT-0000-000N0BD440E		
	80	C4	475	40H	MHBAWT-0000-000N0HC440H	40G	MHBAWT-0000-000N0HC440G		
		D2	510		MHBAWT-0000-000N0HD240H		MHBAWT-0000-000N0HD240G		
	90	B2	380	40H	MHBAWT-0000-000N0UB240H	40G	MHBAWT-0000-000N0UB240G		
B4		410	MHBAWT-0000-000N0UB440H		MHBAWT-0000-000N0UB440G				
3500 K	80	C4	475	35H	MHBAWT-0000-000N0HC435H	35G	MHBAWT-0000-000N0HC435G		
		D2	510		MHBAWT-0000-000N0HD235H		MHBAWT-0000-000N0HD235G		
	90	A2	330	35H	MHBAWT-0000-000N0UA235H	35G	MHBAWT-0000-000N0UA235G		
		A4	355		MHBAWT-0000-000N0UA435H		MHBAWT-0000-000N0UA435G		
3000 K	80	C2	440	30H	MHBAWT-0000-000N0HC230H	30G	MHBAWT-0000-000N0HC230G		
		C4	475		MHBAWT-0000-000N0HC430H		MHBAWT-0000-000N0HC430G		
	90	A2	330	30H	MHBAWT-0000-000N0UA230H	30G	MHBAWT-0000-000N0UA230G		
		A4	355		MHBAWT-0000-000N0UA430H		MHBAWT-0000-000N0UA430G		
2700 K	80	C2	440	27H	MHBAWT-0000-000N0HC227H	27G	MHBAWT-0000-000N0HC227G		
		C4	475		MHBAWT-0000-000N0HC427H		MHBAWT-0000-000N0HC427G		
	90	A2	330	27H	MHBAWT-0000-000N0UA227H	27G	MHBAWT-0000-000N0UA227G		
		A4	355		MHBAWT-0000-000N0UA427H		MHBAWT-0000-000N0UA427G		

Notes


- Cree maintains a tolerance of $\pm 7\%$ on flux and power measurements, ± 0.005 on chromaticity (CCx, CCy) measurements and a tolerance of ± 2 on CRI measurements. See the Measurements section (page 21).
- Cree XLamp MHB-A LED order codes specify only a minimum flux bin and not a maximum. Cree may ship reels in flux bins higher than the minimum specified by the order code without advance notice. Shipments will always adhere to the chromaticity bin restrictions specified by the order code.

RELATIVE SPECTRAL POWER DISTRIBUTION





RELATIVE FLUX VS. JUNCTION TEMPERATURE


Test condition: 9 V, $I_f = 480$ mA; 18 V, $I_f = 240$ mA; 36 V, $I_f = 120$ mA




ELECTRICAL CHARACTERISTICS ($T_j = 85\text{ }^\circ\text{C}$)





ELECTRICAL CHARACTERISTICS ($T_j = 85\text{ }^\circ\text{C}$) - CONTINUED





RELATIVE FLUX VS. CURRENT ($T_j = 85\text{ }^\circ\text{C}$)




RELATIVE FLUX VS. CURRENT ($T_j = 85\text{ }^\circ\text{C}$) - CONTINUED



RELATIVE CHROMATICITY VS. CURRENT (WARM WHITE)




RELATIVE CHROMATICITY VS. CURRENT (WARM WHITE) - CONTINUED




RELATIVE CHROMATICITY VS. TEMPERATURE (WARM WHITE)

Test condition: 9 V, $I_f = 480$ mA; 18 V, $I_f = 240$ mA; 36 V, $I_f = 120$ mA




TYPICAL SPATIAL DISTRIBUTION

Test condition: 9 V, $I_f = 480$ mA; 18 V, $I_f = 240$ mA; 36 V, $I_f = 120$ mA





THERMAL DESIGN

The maximum forward current is determined by the thermal resistance between the LED junction and ambient. It is crucial for the end product to be designed in a manner that minimizes the thermal resistance from the solder point to ambient in order to optimize lamp life and optical characteristics.



THERMAL DESIGN - CONTINUED



PERFORMANCE GROUPS – LUMINOUS FLUX (T_j = 85 °C)

XLamp MHB-A LEDs are tested for luminous flux and placed into one of the following bins.

Group Code	Min. Luminous Flux	Max. Luminous Flux
A2	330	355
A4	355	380
B2	380	410
B4	410	440
C2	440	475
C4	475	510
D2	510	550
D4	550	590
E2	590	635

PERFORMANCE GROUPS – CHROMATICITY

XLamp MHB-A LEDs are tested for chromaticity and placed into one of the regions defined by the following bounding coordinates.


EasyWhite Color Temperatures – 2-Step			
Code	CCT	x	y
40H	4000 K	0.3777	0.3739
		0.3797	0.3816
		0.3861	0.3855
		0.3838	0.3777
35H	3500 K	0.4022	0.3858
		0.4053	0.3942
		0.4125	0.3977
		0.4091	0.3891
30H	3000 K	0.4287	0.3975
		0.4328	0.4064
		0.4390	0.4086
		0.4347	0.3996
27H	2700 K	0.4524	0.4048
		0.4574	0.4140
		0.4633	0.4154
		0.4581	0.4062

PERFORMANCE GROUPS - CHROMATICITY ($T_c = 85\text{ }^\circ\text{C}$) - CONTINUED

EasyWhite Color Temperatures – 3-Step Ellipse						
Bin Code	CCT	Center Point		Major Axis	Minor Axis	Rotation Angle (°)
		x	y	a	b	
50G	5000 K	0.3447	0.3553	0.00840	0.00312	65.0
40G	4000 K	0.3818	0.3797	0.00939	0.00402	53.7
35G	3500 K	0.4073	0.3917	0.00927	0.00414	54.0
30G	3000 K	0.4338	0.4030	0.00834	0.00408	53.2
27G	2700 K	0.4577	0.4099	0.00834	0.00420	48.5


EasyWhite Color Temperatures – 5-Step Ellipse						
Bin Code	CCT	Center Point		Major Axis	Minor Axis	Rotation Angle (°)
		x	y	a	b	
65E	6500 K	0.3123	0.3282	0.01110	0.00550	61.0
57E	5700 K	0.3287	0.3417	0.01230	0.00600	72.0
50E	5000 K	0.3447	0.3553	0.01400	0.00520	65.0
40E	4000 K	0.3818	0.3797	0.01565	0.00670	53.7

CREE'S STANDARD WHITE CHROMATICITY REGIONS PLOTTED ON THE 1931 CIE CURVE



BIN AND ORDER CODE FORMAT


Bin codes and order codes for MHB-A LEDs are configured in the following manner:



REFLOW SOLDERING CHARACTERISTICS

In testing, Cree has found XLamp MHB-A LEDs to be compatible with JEDEC J-STD-020C, using the parameters listed below. As a general guideline, Cree recommends that users follow the recommended soldering profile provided by the manufacturer of solder paste used.

Note that this general guideline may not apply to all PCB designs and configurations of reflow soldering equipment.



IPC/JEDEC J-STD-020C

Profile Feature	Lead-Based Solder	Lead-Free Solder
Average Ramp-Up Rate (T_{Smax} to T_p)	3 °C/second max.	3 °C/second max.
Preheat: Temperature Min (T_{Smin})	100 °C	150 °C
Preheat: Temperature Max (T_{Smax})	150 °C	200 °C
Preheat: Time (t_{Smin} to t_{Smax})	60-120 seconds	60-180 seconds
Time Maintained Above: Temperature (T_L)	183 °C	217 °C
Time Maintained Above: Time (t_L)	60-150 seconds	60-150 seconds
Peak/Classification Temperature (T_p)	215 °C	260 °C
Time Within 5 °C of Actual Peak Temperature (t_p)	10-30 seconds	20-40 seconds
Ramp-Down Rate	6 °C/second max.	6 °C/second max.
Time 25 °C to Peak Temperature	6 minutes max.	8 minutes max.

Note: All temperatures refer to the topside of the package, measured on the package body surface.

NOTES

Measurements

The luminous flux, radiant power, chromaticity and CRI measurements in this document are binning specifications only and solely represent product measurements as of the date of shipment. These measurements will change over time based on a number of factors that are not within Cree's control and are not intended or provided as operational specifications for the products. Calculated values are provided for informational purposes only and are not intended as specifications.

Lumen Maintenance

Cree now uses standardized IES LM-80-08 and TM-21-11 methods for collecting long-term data and extrapolating LED lumen maintenance. For information on the specific LM-80 data sets available for this LED, refer to the public [LM-80 results document](#).

Please read the [Long-Term Lumen Maintenance application note](#) for more details on Cree's lumen maintenance testing and forecasting. Please read the [Thermal Management application note](#) for details on how thermal design, ambient temperature, and drive current affect the LED junction temperature.

Moisture Sensitivity

Cree recommends keeping XLamp LEDs in the provided, resealable moisture-barrier packaging (MBP) until immediately prior to soldering. Unopened MBPs that contain XLamp LEDs do not need special storage for moisture sensitivity.

Once the MBP is opened, XLamp MHB-A LEDs may be stored as MSL 1 per JEDEC J-STD-033, meaning they have unlimited floor life in conditions of ≤ 30 °C/85% relative humidity (RH). Regardless of the storage condition, Cree recommends sealing any unsoldered LEDs in the original MBP.

RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Cree representative or from the Product Documentation sections of www.cree.com.

UL® Recognized Component


Level 4 enclosure consideration. The LED package or a portion thereof has been investigated as a fire and electrical enclosure per ANSI/UL 8750.

Vision Advisory


WARNING: Do not look at exposed lamp in operation. Eye injury can result. For more information about LEDs and eye safety, please refer to the [LED Eye Safety application note](#).

MECHANICAL DIMENSIONS


All measurements are $\pm .13$ mm unless otherwise indicated.




Top View




Side View




Bottom View



Alternate Bottom View



Recommended PCB Solder Pad




**Recommended Stencil Pattern
(Shaded Area Is Open)**

TAPE AND REEL


All Cree carrier tapes conform to EIA-481D, Automated Component Handling Systems Standard.

All dimensions in mm.




PACKAGING

Unpackaged Reel



Label with Cree Bin Code, Qty, Reel ID


Packaged Reel



Label with Cree Order Code, Qty, Reel ID, PO #

Label with Cree Bin Code, Qty, Reel ID

Boxed Reel



Label with Cree Order Code, Qty, Reel ID, PO #

Label with Cree Bin Code, Qty, Reel ID

Patent Label