

**Modul LLE G2 24mm 2000lm SNC**

Modules LLE ESSENCE


**Product description**

- \_ Optimal solution for linear and panel lights where cost is main priority, together with the new LC Ip SNC and ADV LED Driver provides best system efficiency
- \_ Typ. luminous flux 2,000 and 4,000 lm
- \_ Efficacy of the module up to 171 lm/W
- \_ High colour rendering index CRI > 80
- \_ Small colour tolerance (MacAdam 4) <sup>①</sup>
- \_ Colour temperatures 3,000, 4,000 and 6,500 K
- \_ Module dimension 24 x 280 mm and 24 x 560 mm (ZHAGA compliant)
- \_ Perfectly uniform light, even if several LED modules are used together in a line
- \_ Push terminals for quick and simple wiring of LED module to LED module
- \_ Broad portfolio from extruded lenses and covers available
- \_ Simple installation via clips or screws
- \_ Long life-time up to 50,000 hours
- \_ 5-year guarantee

① Integral measurement over the complete module.

**Website**

<http://www.tridonic.com/28002293>



Spotlights



Downlights



Linear



Area



Floor | Wall



Free-standing



Street



Decorative




High bay

**Modul LLE G2 24mm 2000lm SNC**

Modules LLE ESSENCE

The complete data sheet for this product is available in the Downloads section.

**Ordering data**

Type	Article number	Colour temperature	Packaging, carton	Weight per pc.
LLE G2 24x560mm 4000lm 840 2T SNC	28002293	4000 K	200 pc(s).	0.042 kg

**Technical data**

Beam characteristic	120°
Ambient temperature range	-40 ... +60 °C
tp rated	65 °C
tc	85 °C
Irated	325 mA
Imax	540 mA
Max. permissible LF current ripple	540 mA
Max. permissible peak current	1,200 mA / max. 10 ms
Max. working voltage for insulation <sup>®</sup>	335 V
Insulation test voltage	1,67 kV
CTI of the printed circuit board	≥ 600
ESD classification	Severity level 4
Risk group (EN 62471:2008)	RG0
Classification acc. to IEC 62031	Built-in
Type of protection	IP00

**Approval marks****Standards**

IEC 62031, IEC 62471, IEC 62778, IEC 62717, IEC 61547

## Specific technical data

Type <sup>®</sup>	Photometric code	Typ. luminous flux at tp = 25 °C <sup>②</sup>	Typ. luminous flux at tp = 65 °C <sup>③</sup>	Typ. forward current	Min. forward voltage at tp = 65 °C	Max. forward voltage at tp = 25 °C	Typ. power consumption at tp = 65 °C	Luminous efficacy module at tp = 25 °C	Luminous efficacy module at tp = 65 °C	Luminous efficacy system at tp = 65 °C	Colour rendering index CRI
<b>Operating mode HE at 200 mA</b>											
LLE G2 24x560mm 4000lm 840 2T SNC	840/469	2,750 lm	2,560 lm	200 mA	72.8 V	90.2 V	15.9 W	171 lm/W	163 lm/W	147 lm/W	> 80
<b>Operating mode HE at 250 mA</b>											
LLE G2 24x560mm 4000lm 840 2T SNC	840/469	3,370 lm	3,140 lm	250 mA	74.4 V	92.2 V	20.3 W	164 lm/W	156 lm/W	140 lm/W	> 80
<b>Operating mode NM at 325 mA</b>											
LLE G2 24x560mm 4000lm 840 2T SNC	840/469	4,270 lm	3,980 lm	325 mA	76.8 V	95.2 V	27.2 W	154 lm/W	146 lm/W	131 lm/W	> 80
<b>Operating mode HO at 400 mA</b>											
LLE G2 24x560mm 4000lm 840 2T SNC	840/469	5,130 lm	4,770 lm	400 mA	79.1 V	98.0 V	34.5 W	146 lm/W	138 lm/W	124 lm/W	> 80
<b>Operating mode HO at 450 mA</b>											
LLE G2 24x560mm 4000lm 840 2T SNC	840/469	5,670 lm	5,270 lm	450 mA	80.6 V	99.8 V	39.5 W	141 lm/W	134 lm/W	121 lm/W	> 80

② If mounted with M4 screws and plastic washers.

③ HE ... high efficiency, NM ... nominal mode, HO ... high output.

④ Tolerance range for optical and electrical data: ±10 %.