

GUANGZHOU YOUXIANTONG TRADE CO., LTD.
O/B NINGBO OUTLUX ELECTRICAL CO.,LTD

ADD.: JINXI VILLAGE,HENGXI TOWN, YINZHOU DISTRICT,
NINGBO, 315131,CHINA
TEL:88366978

PACKING LIST

Shipping mark:Rafeed

AHMED ABID AL-SHEIKH Trading CO.
KILIO-08, OLD MAKKAH ROAD JEDDAH- SAUDI ARABIA
TURKY AHMAD ABED ALSHEIKH
TEL: 00966 1262 04787 MOB. 00966505600512
MOB. 00966126205171 FAX: 00966126200258
EMAIL:AAALSHEIKHEST@GMAIL.COM
IMPORTER NO.3140436
VAT NO.311271998100003
Zip code 22349
district code 00966
CR.NO. 4030028786 / 7013479022

Description:

Country 国家	ITEM NO型号	Item 产品	QUANTITY	QTY/CT	CTN箱数	N.W.净重	G.W.毛重	Total N.W. 总净重	Total G.W. 总毛重	CTN SIZE外箱尺寸CM			Volume 体积	Total Volume 总体积
			TY订单数	N 箱数						L长	W宽	H高		
1	ES-0897A	Tri-proof Housing IP65, 9W for T8 DOUBLE-END wiring ABS base, PC cover, with stainless steel clips, T8 lamp holder (UL), without LED tube, Dimensions: 670x68x84 mmCertified CB	980	20	49.00	10.00	10.60	490.00	519.40	68.00	29.00	32.00	0.06	3.09
2	ES-0896A	Tri-proof Housing IP65, 2*9W for T8 DOUBLE-END wiring ABS base, PC cover, with stainless steel clips, T8 lamp holder (UL), without LED tube, Dimensions: 670x104x84 mmCertified CB	435	15	29.00	11.10	12.00	321.90	348.00	68.00	33.00	32.00	0.07	2.08
3	ES-0898A	Tri-proof Housing IP65, 18W for T8 DOUBLE-END wiring ABS base, PC cover, with stainless steel clips, T8 lamp holder (UL), without LED tube, Dimensions: 1270x68x84mmCertified CB	1476	12	123.00	11.60	12.50	1426.80	1537.50	129.00	22.00	26.00	0.07	9.08
4	ES-0899A	Tri-proof Housing IP65, 2*18W for T8 DOUBLE-END wiring ABS base, PC cover, with stainless steel clips, T8 lamp holder (UL), without LED tube, Dimensions: 1270x104x84mmCertified CB	1480	10	148.00	12.50	13.00	1850.00	1924.00	129.00	22.00	31.00	0.09	13.02
5	AS30139-1	E-Series - Anis - Floodlight Mounted with bracket 30watt 3000K - CRI 70 2400Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W185 x L158 x H25mm Transparent / Glass (Front Cover) - White / Aluminum (Housing) - 485g - Warranty 3 YearsCertified CB	940	20	47.00	9.30	11.00	437.10	517.00	34.00	34.00	20.00	0.02	1.09



6	AS60140-1	E-Series - Anis - Floodlight Mounted with bracket 30watt 6000K - CRI 70 2550Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W185 x L158 x H25mm Transparent / Glass (Front Cover) - White / Aluminum (Housing) - 485g - Warranty 3 YearsCertified CB	1960	20	96.00	9.30	11.00	911.40	1078.00	34.00	34.00	20.00	0.02	2.27
7	AS30145-1	E-Series - Anis - Floodlight Mounted with bracket 50watt 3000K - CRI 70 4000Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W230 x L195 x H30mm Transparent / Glass (Front Cover) - White / Aluminum (Housing) - 820g - Warranty 3 YearsCertified CB	1470	10	147.00	8.30	10.00	1220.10	1470.00	39.00	25.00	22.00	0.02	3.15
8	AS60146-1	E-Series - Anis - Floodlight Mounted with bracket 50watt 6000K - CRI 70 4250Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W230 x L195 x H30mm Transparent / Glass (Front Cover) - White / Aluminum (Housing) - 820g - Warranty 3 YearsCertified CB	2980	10	298.00	8.30	10.00	2473.40	2980.00	39.00	25.00	22.00	0.02	6.39
9	AS30147-1	E-Series - Anis - Floodlight Mounted with bracket 100watt 3000K - CRI 70 8000Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W297 x L242 x H32mm Transparent / Glass (Front Cover) - White / Aluminum (Housing) - 1540g - Warranty 3 YearsCertified CB	2230	5	446.00	7.70	8.50	3434.20	3791.00	32.00	24.00	27.00	0.02	9.25
10	AS60148-1	E-Series - Anis - Floodlight Mounted with bracket 100watt 6000K - CRI 70 8500Lumen - 0.9PF 176 To 265V IP 65 - Rectangular W297 x L242 x H32mm Transparent / Glass (Front Cover) - White / Aluminum (Housing) - 1540g - Warranty 3 YearsCertified CB	4230	5	846.00	7.70	8.50	6514.20	7191.00	32.00	24.00	27.00	0.02	17.54
11	AS30133-1	E-Series - Anis - Floodlight Mounted with bracket 10watt 3000K - CRI 70 800Lumen - 0.8PF 176 To 265V IP 65 - Rectangular W127 x L120 x H23mm Transparent / Glass (Front Cover) - White / Aluminum (Housing) - 250g - Warranty 3 YearsCertified CB	540	60	9.00	14.00	14.90	126.00	134.10	41.00	31.00	30.00	0.04	0.34
Total:			18721		2240.00			19205.10	21490.00					67.30

2240.00

21490.00

67.30

0

0

0.002928

